



PLT1M-M



- For indoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- A variety of materials and colors available for specific applications
- Miniature to Standard cross sections feature a curved tip for easy threading and handling

▪ Part Number	PLT1M-M
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Cable Tie, 3.9", Miniature cross section
▪ Product Type	Cable Ties
▪ Material	Nylon 6.6
▪ Color	Natural
▪ CSA Certified	Yes
▪ Mil. Std. Part Number	MS3367-4-9
▪ UL Listed (File #E56854)	Yes
▪ UL Recognized (File #E56854)	Yes
▪ Length (In.)	3.9
▪ Length (mm)	99
▪ Width (In.)	.098
▪ Width (mm)	2.5
▪ CE Compliant	Yes
▪ Cross Section	Miniature
▪ Head Height (In.)	.154
▪ Head Height (mm)	3.9
▪ Head Width (In.)	.180
▪ Head Width (mm)	4.6
▪ Locking Style	Locking
▪ Material Flammability Rating	UL 94V-2
▪ Max. Bundle Diameter (In.)	.87
▪ Max. Bundle Diameter (mm)	22
▪ Max. Continuous Use Temperature	185°F (85°C)
▪ Min. Loop Tensile Strength (Lbs.)	18
▪ Min. Loop Tensile Strength (N)	80

■ Pricing Description	Cable Tie, 3.9"L (99mm), Miniature, Nylon, Natural
■ Thickness (In.)	.043
■ Thickness (mm)	1.1
■ Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
■ Min. Order UOM	PC
■ Min. Order Qty.	1000
■ BOM Qty. (# of Pkgs.)	

