



Static Control Workstation Solutions

Product No. Description

	<p>3041 Grounding Kit for Static Protective Hard Laminate includes #10 screw, lock washer, #10 nut, lock washer wing nut, #10 self-tapping screw and one 10 ft. (3,0 m) ground cord. Ground cord has a 1-megohm resistor.</p>
	<p>3042 Wrist Strap Grounding System. Grounds two single conductor wrist straps and conveniently mounts beneath the edge of most work benches. Comes complete with 10 ft. (3,0 m) ground cord.</p>
	<p>3043 Interconnect Cord 5 ft. (3,5 m), with 10 mm. Snap molded-in male snap fastener at each end. Connects all 3M™ static control mats and runners to each other. Ground cord has a 1-megohm resistor.</p>
	<p>3047 Common Point Grounding System, 10 ft (3m) to ground workstation components. Single-row, six-terminal strip, protective cover, three cable clips. Ground cord has a 1-megohm resistor.</p>
	<p>3048 Grounding System for Wrist Strap/Table Mat. Easily snaps onto mats and runners, (10 mm snap); grounds two single conductor wrist straps. Comes complete with ring connector and 15 ft. (4,6 m) ground cord. Ground cord has a 1-megohm resistor for mat connection only.</p>
	<p>3050 Snap Fastener, female, 10 mm diameter. For 3M™ table and floor mats and runners 8200 series.</p>
	<p>3051 Ground Cord with center snap for standard field service kits. Wrist strap cord section 10 ft. (3,0 m) and ground cord section 5 ft. (1,5 m). Each contains a 1-megohm resistor.</p>
	<p>3057 Monitor Stand-By Jack. Allows operator to disconnect a ground cord from the wrist band and leave the workstation without deactivating the 3M™ Workstation Monitor 724 or 3M Static Monitor 790.</p>
	<p>8001 Cleaner for Static Control Mats. One quart (32 oz.) trigger-spray bottle or 5-gallon jug with spigot. An extra-strength cleaner for removing dirt and stains from all types of static control surfaces, including table and floor mats, hard laminate bench tops and portable field service kits. It will also remove difficult grime from epoxy or tile flooring. Used full strength, it is a clear, colorless, water-based liquid that leaves no tacky or corrosive residue. Read all Health Hazard Precautionary and First Aid statements found in the Material Safety Data sheet and/or product label prior to handling or using. Refer to www.3M.com to obtain copy of MSDS.</p>

Phone: 1-800-328-1368 or www.3M.com/esd



Static Control Workstation Solutions

Dual Conductor Fabric Wrist Straps for Monitors

The 3M™ Dual Conductor Fabric Wrist Strap 2368 is used exclusively with the 3M™ Workstation Monitor 724 and 3M™ Wrist Strap Monitor 725.

One size adjusts to any size wrist to provide reliable protection. The wrist strap features a band made of a silver plated, monofilament, continuous thread woven together with elastic nylon to maintain full conductivity, comfort and reliability, while providing rapid and continuous drain of static charge. Two-one megohm resistors are built into the ground cord. Adjustability also simplifies ordering procedures and inventory control by eliminating the need to order and stock several band sizes.



Fabric Wrist Band 2368

Note: The 3M 2300 Series, 2300VM Series and 2200 Series bands and cords are not interchangeable. See page 8 for additional information on wrist band and cord combinations.

Product No.	Description
2368	Turquoise Dual Conductor Adjustable Fabric Wrist Band.
2368VM	Turquoise Dual Conductor Adjustable Fabric Wrist Band.
2360	Dual Conductor Coiled Cord, 5 ft. (1,5 m) practical length.
2370	Dual Conductor Coiled Cord, 10 ft. (3,0 m) practical length.
2371	Dual Conductor Coiled Cord, 20 ft. (6,0 m) practical length.

Warning:

These products are not to be used in areas where the individual may come in contact with exposed circuitry exceeding 250 Volts AC.

These products are for static control. It will not reduce or increase your risk of receiving electrical shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the 3M Wrist Strap.
- A current limiting resistor(s) is located in these 3M Ground Cords. DO NOT REMOVE. If the resistor(s) become damaged, replace ground cord immediately.

Dual Conductor Metal Wrist Straps for Monitors

The 3M Dual Conductor Metal Wrist Straps 2300 Series are for use exclusively with the Workstation Monitors 724 and Wrist Strap Monitor 725. These long lasting metal expansion bands are for use in clean rooms and applications requiring extended band life.

Three sizes are available: small for wrists from 4.5 in. to 6 in. (114 mm to 152 mm) in circumference; medium for wrists from 5.5 in. to 7.25 in. (140 mm to 184 mm); and large for wrists larger than 6.5 in. (165 mm).



Metal Wrist Strap 2381

Note: The 3M Bands and Cords 2300 Series, 2300VM Series, and 2200 Series are not interchangeable. See page 8 for additional information on wrist band and cord combinations.

Product No.	Description
2381	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Small)
2381VM	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Small)
2382	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Medium)
2382VM	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Medium)
2383	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Large)
2383VM	Dual Conductor Metal Wrist Strap. Includes band and 5 ft. (1,5 m) cord. (Large)
2384	Dual Conductor Metal Wrist Band. (Small)
2384VM	Dual Conductor Metal Wrist Band. (Small)
2385	Dual Conductor Metal Wrist Band. (Medium)
2385VM	Dual Conductor Metal Wrist Band. (Medium)
2386	Dual Conductor Metal Wrist Band. (Large)
2386VM	Dual Conductor Metal Wrist Band. (Large)
2360	Dual Conductor Coiled Cord, 5 ft. (1,5 m) practical length.
2370	Dual Conductor Coiled Cord, 10 ft. (3,0 m) practical length.
2371	Dual Conductor Coiled Cord, 20 ft. (6,0 m) practical length.