

Scotch® Premium Heavy Duty Packaging Tape 3750 • 3750-RD



Technical Data

April, 2003

Product Description Scotch® Premium Heavy Duty Packaging Tape 3750 and 3750-RD is a superior performance packaging tape used for box sealing, splicing, reoperation and other demanding packaging applications. This product has a strong conformable backing and the most consistent pressure sensitive hot melt adhesive system available. This time proven construction assures superior performance in a wide range of environments and applications.

Construction	Backing	Adhesive	Colors
	Biaxially oriented 3M™ Scotchpro™ polypropylene film	Pressure sensitive hot melt rubber-resin	Clear and Tan

Typical Physical Properties		ASTM Test Method
Adhesion to Steel:	55 oz./in. width (60 N/100 mm width)	D-3330
Tensile Strength:		
Machine Direction:	35 lbs./in. width (613 N/100 mm width)	D-3759
Cross Direction:	70 lbs./in. width (1226 N/100 mm width)	D-3759
Elongation at Break:	160%	D-3759
Thickness - Backing:	2.0 mil (0.051 mm)	D-3652
Total:	3.1 mil (0.079 mm)	D-3652
Holding Power to Fiberboard:	12,000 + minutes	D-3654

- Features**
- Meets CID A-A-1684B and ASTM D5486 Type III.
 - Considered water-resistant as per ASTM D5570.
 - Adheres instantly to most surfaces including cartons containing high levels of recycled content.
 - A strong conformable backing with high edge tear and split resistance.
 - Complies with the environmental considerations of ASTM D 1974-92.
 - Superior performance ensures reliable closures.
 - Available in bulk or with reusable dispenser.
 - Dispenser doesn't allow tape to fall back onto roll.

Scotch® Premium Heavy Duty Packaging Tape

3750 • 3750-RD

Available Sizes	Standard Widths:	Scotch® Tape 3750 – 36 mm, 48 mm Scotch® Tape 3750-RD – 48 mm
	Core Size (ID):	3 in.
	Lengths:	50 m, bulk

Application Techniques An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Premium Heavy Duty Packaging Tape 3750 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, Scotch® Tape 3750 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage Conditions Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2003 (4/03)