



Search This Product Catalog

[Product Catalog for Innovative Solutions](#) > [3M™ Telecommunications / Network Products](#) > [Fiber Connectors, Splices, Couplings and Cable Assemblies](#) > [Fiber Connectors and Couplings](#) > [FC Connectors and Couplings](#) > [Epoxy FC Connectors](#) >

 [Printer-friendly format](#) **6202 Connector FC/PC MM**



The FC/PC Connector is a field mountable, pull-proof connector that is fully compatible with all FC connectors adhering to the NTT specification.

[\[click to enlarge\]](#)

3M Id : 80-6107-6540-8
GTIN(UPC/EAN) : 0 00 54007 91716 8

Additional Information

The FC/PC connector maximizes termination yield through ease of mounting and a high performance polishing procedure. The three-piece connector design (connector, crimp ring, and boot) is mounted using the same simple process used for other 3M connectors. The FC/PC connector is available in single-mode and multimode utilizing epoxy adhesive. It is also available in multimode preloaded with 3M's

[Full Text . . .](#)

Learn More . . .

- [Packaging Data](#)
- [FC Connector](#)
- [FC Hot Melt Connector - Illustration/Line Art](#)
- [FC/PC Connector and Accessories - Illustration/Line Art- \(TIFF\)](#)
- [FC/PC Connector and Accessories - Illustration/Line Art- \(TIFF\)](#)
- [FC/PC Connector Features and Benefits - Features and Benefits- \(JPG\)](#)
- [FC_PC Connector Diagram - Illustration/Line Art- \(JPG\)](#)
- [Fiber Optic ST and FC Connectors - Instructions/Manual \(PDF 662.8 K\)](#)
- [SC & FC/PC3 Pull-Proof Fiber Optic Connectors - Instructions/Manual \(PDF 729.2 K\)](#)
- [SC&FC/PC3 Pull-Proof Fiber Optic Connectors - Instructions/Manual \(PDF 205.6 K\)](#)
- [SC_FC_ST Hot Melt Fiber Optic Connectors - Instructions/Manual \(PDF 534.1 K\)](#)

Please Note:
Adobe® Acrobat® Reader is required to view PDF documents.



Government Solutions Catalogs

Product Catalog for Innovative Solutions

- [3M™ Aircraft Products](#)
- [3M™ Electrical Products](#)
- [3M™ Environmental Protection, Clean Up and Safety Products](#)
- [3M™ Government Facilities Products](#)
- [3M™ Government Vehicle Products](#)
- [3M™ Homeland Security and Homeland Defense Products](#)
- [3M™ Medical Center Products](#)
- [3M™ Meetings, Presentations & Training Products](#)
- [3M™ Office Products](#)
- [3M™ Safety / Security Products](#)
- [3M™ Ships/Fleet Products](#)
- [3M™ Telecommunications / Network Products](#)
- [3M™ Weapons System Protection](#)

Other Tools

- [MSDS Search](#)
- [Government Contracts](#)

Characteristics

Boot Material	Polyester
Flame Retardant	UL-94 V-O

Operating Temperature Range	-40 to 85 Degree Celsius
Primary Trademark Name	3M
Storage Temperature	-40 to 85 Degree Celsius