

[Product Catalog for Government Solutions](#) > [3M™ Electrical Products](#) . . . [3M™ Scotchlok™ Butt Connectors](#)
 > [3M™ Scotchlok™ Butt Connectors Vinyl Insulated Seamless](#) >

 [Printer-friendly format](#) **3M™ Scotchlok™ Vinyl Insulated Seamless Butt Connector MV10BCX, 12-10 AWG**

This connector has a wire range of 12-10 AWG and inner unit pack of 50 with a case quantity of 500. This butt connector uses chamfered barrel ends to provide fast easy wire insertion from both ends and a built in wire stop for correct positioning. It must be crimped at ends.


GTIN(UPC/EAN) : 0 00 54007 24027 3
 3M Id : 80-6100-0189-5
 Buyer's Part Number : 24027

Additional Information

Learn More . . .

[Packaging Data](#)
[3M™ Scotchlok™ Terminals MV18BC, MV14BC, MV10BC - Data Sheet \(PDF 25.5 K\)](#)
[Recommended Stranded Wire Combinations - Product Selection Guide \(PDF 5.7 K\)](#)
[Terminal Stud Size Chart - Product Selection Guide \(PDF 5.2 K\)](#)

Please Note:
 Adobe® Acrobat® Reader is required to view PDF documents.



Characteristics

Agency Approvals	UL and CSA
Barrel Style	Seamless
China RoHS - Below MCV	No
CSA File Number	LR22190
EU RoHS Compliant	No
Insulation Material	Vinyl

▼ **Government Solutions Catalogs**

▼ **Product Catalog for Government Solutions**

- 3M™ Aircraft Products
- 3M™ Electrical Products
- 3M™ Environmental Protection, Clean Up and Safety Products
- 3M™ Government Facilities Products
- 3M™ Government Vehicle Products
- 3M™ Homeland Security and Homeland Defense Products
- 3M™ Medical Center Products
- 3M™ Meetings, Presentations & Training Products
- 3M™ Office Products
- 3M™ Safety / Security Products
- 3M™ Ships/Fleet Products
- 3M™ Telecommunications / Network Products
- 3M™ Weapons System Protection
- Emergency Preparedness, Response & Recover

◦ **Other Tools**

- MSDS Search
- Government Contracts


Terminal Style	Standard
Terminal Type	Butt
UL File Number	E23438
Wire Gauge Range	10 to 12 American Wire Gauge (AWG)



Scotchlok™ Terminals

MV18BC, MV14BC, MV10BC

Butt Connector, Vinyl Insulated, Seamless



Data Sheet

Product Number	Wire Range (AWG)	L (in.)	Thickness	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
MV18BC	22-18	1.02	0.031	0.28	0.062	0.125
MV14BC	16-14	1.02	0.031	0.30	0.095	0.155
MV10BC	12-10	1.20	0.038	0.38	0.142	0.218



UNDERWRITERS
LABORATORIES
STANDARD NO. UL 486C
3M FILE NO. E23438



CANADIAN STANDARDS
ASSOCIATION
STANDARD NO. 22.2
NO. 0, 65
3M FILE NO. LR22190

Installation Information

⚠ WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.


Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style) or TR-490 (ratchet style) hand tools.

Specifications

Wire Size:
Barrel Seam:
Insulator Max. Volt. Rating:

See Table Above
Seamless
600 V Building Wire
1000 V Signs or
Fixtures (Luminaires)
221°F (105°C)
Same as Wire
Vinyl
ETP Copper
Tin

Maximum Operating Temp:
Maximum Current:
Insulator Material:
Terminal Material:
Terminal Plating:



● Barrel Crimp (Electrical)

Engineering Specification

Crimp-type connectors shall, electrically and mechanically, connect permanently to the pre-stripped ends of two stranded copper wires.

The connector line shall offer barrel variations in wire (AWG) size (22-18, 16-14, 12-10). and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated seamless, etc...). The connector line shall have regulatory agency coverage (UL Listing, CSA Certification). The connectors shall be marked with the wire range and manufacturer's symbol (↑).

The Vinyl Insulated, Seamless Butt Connector shall be tin-plated, annealed copper, having a double-length, round seamless barrel, with a center stop and a close fitting vinyl tube covering, color coded and sized for a specified (AWG) wire range (22-18, 16-14, 12-10).

Insulated connectors shall be UL Listed and CSA Certified for 600 volts maximum, building wire: 1000 volts maximum, signs or fixtures and temperature rated 221°F (105°C) maximum.

3M and Scotchlok are trademarks of 3M.



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

3M

Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
<http://www.3M.com/elpd>