3M United States


3M Worldwide : United States : Electronics Manufacturing

- Solutions for Electronic **Specialty Markets** (ESM)
 - Product Catalog for Electronic Specialty Markets
 - 3M[™] Electronic Specialty Markets - New Product Releases
 - 3M[™] Abrasives
 - 3M[™] Adhesives,
 - **Cleaners & Compounds** • 3M[™] Breadboards &
 - **Test Clips** 3M[™] Cable &
 - Assemblies
 - 3M[™] Copper Interconnects
 - 3M[™] Fiber Optics • 3M[™] Fire Protection
 - 3M[™] Heat Shrink

 - 3M[™] Identification Systems
 - 3M[™] Occupational Health & Safety Products
 - 3M[™] Protective **Bumpers**
 - 3M[™] Reclosable Fasteners
 - 3M[™] Splicing, **Terminating & Ducting**
 - 3M[™] Static Control
 - 3M[™] Tapes
 - 3M[™] Terminals, Kits & Tools
 - 3M[™] Vacuums & Accessories
 - 3M[™] Warehousing & Packaging Supplies
 - 3M[™] Wire Connectors

Product Catalog for Electronic Specialty Markets > 3M[™] Terminals, Kits & Tools > Forks > Scotchlok[™] Locking Fork Terminals - Vinyl Insulated Butted Seam >

Printer-friendly format 3M[™] Scotchlok[™] Vinyl Insulated Butted Seam Locking Fork Terminal MVU18-6FLK, Stud Size 6



w

This terminal has a wire range of 22-18 AWG and a stud size of 6. It comes in case quantities of 1000 per case.



GTIN(UPC/EAN) : 0 00 54007 01360 0 3M Id: 80-6100-4003-4

Additional Information

The spring-like tongue locks into place around the stud even when the mount screw is not tightened. Extra force is required to remove it from the stud.

Learn More . . . Packaging Data Locking Forks - Vinyl Insulated Butted Seam 22-18 AWG - Product Selection Guide (PDF 26.0 K) Scotchlok Terminals MVU18-4FL THRU MVU10-14FL -Data Sheet (PDF 19.9 K) Terminal Stud Size Chart - Product Selection Guide (PDF 5.2 K) Please Note: Adobe® Acrobat® Reader is required to view PDF documents. Get Acrobat. Reader

other Tools


- What's New
- Sales Contacts
- U.S. Distributors

Characteristics	
Agency Approvals	UL and CSA
Barrel Style	Butted
China RoHS - Below MCV	No
CSA File Number	LR22190
EU RoHS Compliant	No

Insulation Material	Vinyl
Stud Size	6 American Wire Gauge (AWG)
Terminal Style	Locking
Terminal Type	Fork
UL File Number	E23438
Wire Gauge Range	18 to 22 American Wire Gauge (AWG)

3M Scotchlok[™] Terminals

MVU18-4FL thru MVU10-14FL Locking Fork, Vinyl Insulated, Butted Seam



Data Sheet

Product Number	Wire Range (AWG)	Stud Size	Max Lock Width	w	с	L	E	Thickness	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
MVU18-4FL	22-18	4	0.27	0.25	0.25	0.88	0.70	0.030	0.25	0.070	0.145
MVU18-6FL	22-18	6	0.27	0.25	0.25	0.88	0.70	0.030	0.25	0.070	0.145
MVU18-8FL	22-18	8	0.34	0.30	0.25	0.88	0.70	0.030	0.25	0.070	0.145
MVU18-10FL	22-18	10	0.35	0.32	0.25	0.88	0.70	0.030	0.25	0.070	0.145
MVU14-4FL	16-14	4	0.27	0.25	0.25	0.88	0.70	0.030	0.25	0.090	0.170
MVU14-6FL	16-14	6	0.27	0.25	0.25	0.88	0.70	0.030	0.25	0.090	0.170
MVU14-8FL	16-14	8	0.34	0.30	0.25	0.88	0.70	0.030	0.25	0.090	0.170
MVU14-10FL	16-14	10	0.35	0.32	0.25	0.88	0.70	0.030	0.25	0.090	0.170
MVU14-14FL	16-14	1/4	0.48	0.43	0.40	1.10	0.85	0.030	0.25	0.090	0.170
MVU10-6FL	12-10	6	0.30	0.28	0.28	1.03	0.83	0.040	0.25	0.135	0.250
MVU10-8FL	12-10	8	0.35	0.32	0.28	1.03	0.83	0.040	0.25	0.135	0.250
MVU10-10FL	12-10	10	0.36	0.32	0.28	1.03	0.83	0.040	0.25	0.135	0.250
MVU10-14FL	12-10	1/4	0.48	0.43	0.44	1.24	0.99	0.040	0.25	0.135	0.250



LISTED 314R UNDERWRITERS LABORATORIES STANDARD NO. UL 486A 3M FILE NO. E23438

Specifications

Wire Size: Barrel Seam: Max. Voltage Rating:

Max. Temperature Rating: Max. Current: Insulator Material: Terminal Material: Plating: CANADIAN STANDARDS

ASSOCIATION STANDARD NO. C22.2 NO. 0. 65 3M FILE NO. LR22190

See Table Above Butted 600 V Building Wire 1000 V Signs, Fixtures and Luminaires 221°F (105°C) Same as Wire Vinyl ETP Copper Tin

Installation Information

WARNING


Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style), or TR-490 (ratchet style) hand tools.





Engineering Specification

Crimp-type terminals shall, electrically and mechanically, connect to a pre-stripped end of a stranded copper wire: and have a flat tongue portion with a central opening for mounting around a screw or stud.

The terminal line shall offer tongue variations in hole (stud) size (6, 8 10, etc.) and configuration (ring, fork, block fork, flanged block fork, locking fork, etc.): and barrel variations in wire (AWG) size (22-18, 16-14, 12-10, etc.) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated with insulation grip, etc.). The terminal line shall have regulatory agency coverage (UL Listing, CSA Certification). The terminal tongue shall be marked with the wire range and manufacturer's symbol (↑).

The vinyl-insulated, butted seam locking fork terminal shall be tin-plated, annealed copper, with the tongue having a specified stud slot (size 4 thru 1/4 in.) and a butted seam barrel covered by a molded vinyl funnel entry sleeve, color coded and sized, for a specified (AWG) wire range (22-18, 16-14, 12-10).

Insulated terminals shall be UL Listed and CSA Certified for 600 Volts maximum building wire: 1000 Volts maximum in signs, fixtures and luminaries and have a maximum operating temperature of 221°F (105°C).

3M and Scotchlok are trademarks of 3M

IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.

ЗМ

Electrical Products Division 6801 River Place Blvd. Austin, TX 78726-9000 http://www.3M.com/elpd