

3M Worldwide : United States : Electronics Manufacturing

- Solutions for Electronic Specialty Markets (ESM)
 - Product Catalog for Electronic Specialty Markets
 - 3M™ Electronic
 Specialty Markets New
 Product Releases
 - 3M™ Abrasives
 - 3M™ Adhesives,
 Cleaners & Compounds
 - 3M™ Breadboards & Test Clips
 - 3M™ Cable & Assemblies
 - 3M™ Copper Interconnects
 - 3M™ Fiber Optics
 - 3M™ Fire Protection
 - 3M™ Heat Shrink
 - 3M™ Identification Systems
 - 3M™ Occupational Health & Safety Products
 - 3M[™] Protective Bumpers
 - 3M™ Reclosable Fasteners
 - 3M™ Splicing, Terminating & Ducting
 - 3M™ Static Control
 - 3M™ Tapes
 - 3M™ Terminals, Kits & Tools
 - 3M™ Vacuums & Accessories
 - 3M™ Warehousing & Packaging Supplies
 - 3M™ Wire Connectors

Product Catalog for Electronic Specialty Markets > 3M™ Terminals, Kits & Tools > Butt Connectors > 3M™ Scotchlok™ Butt Connectors - Vinyl Insulated Butted Seam >

□ Printer-friendly format 3MTM ScotchlokTM Vinyl Insulated Butted Seam Butt Connector MVU18BCK, 22-18 AWG

This connector has a wire range of 22-18 AWG and a case quantity of 1000.

GTIN(UPC/EAN): 0 00 54007 01315 0

3M Id: 80-6100-3935-8

Additional Information

This butt connector uses chamfered barrel ends to provide fast easy wire insertion from both ends and a built in wire stop for correct positioning. It must be crimped at ends.

Learn More . . .

Packaging Data

3M™ Scotchlok™ Terminals MVU18BC, MVU14BC, MVU10BC - Data Sheet (PDF 136.1 K)

<u>Butt Connectors - Vinyl Insulated Butted Seam - Product Selection Guide (PDF 12.5 K)</u>

Recommended Stranded Wire Combinations - Product Selection Guide (PDF 5.7 K)

Scotchlok Connectors MVU18PC, MVU14PC, MVU10PC - Data Sheet (PDF 13.9 K)

<u>Terminal Stud Size Chart - Product Selection Guide (PDF 5.2 K)</u>

Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



Other Tools

- What's New
- Sales Contacts
- U.S. Distributors

Characteristics


Agency Approvals	UL and CSA
Barrel Style	Butted
China RoHS - Below MCV	No
CSA File Number	LR22190
EU RoHS Compliant	No
Insulation Material	Vinyl

Terminal Style	Standard
Terminal Type	Butt
UL File Number	E23438
Wire Gauge Range	18 to 22 American Wire Gauge (AWG)



Scotchlok[™] Terminals

MVU18BC, MVU14BC, MVU10BC Butt Connector, Vinyl Insulated, Butted Seam



Data Sheet

Product Number	Wire Range (AWG)	L	Thickness	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
MVU18BC	22-18	1.00	0.030	0.25	0.070	0.145
MVU14BC	16-14	1.00	0.030	0.25	0.090	0.170
MVU10BC	12-10	1.02	0.040	0.25	0.135	0.250



UNDERWRITERS LABORATORIES STANDARD NO. UL 486C 3M FILE NO. E23438



CANADIAN STANDARDS ASSOCIATION STANDARD NO. 22.2 NO. 0, 65 3M FILE NO. LR22190

Installation Information

∆WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 5/16 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style) or TR-490 (ratchet style) hand tools.



■ Barrel Crimp (Required)

Specifications

Maximum Current:

Insulator Material:

Wire Size: See Table Above Barrel Seam: Butted
Insulator Max. Volt Rating: 600 V Building V

600 V Building Wire: 1000 V Signs or

Fixtures (Luminaires) 221°F (105°C) Same as Wire

Same as Wire Vinyl ETP Copper

Terminal Material: ETF Terminal Plating: Tin

Maximum Operating Temp.:

3M is a trademark of 3M Company.

(Ų

is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, Indirect, special, Incidental or consequential regardless of the legal theory asserted.

3M

Electrical Markets Division 6801 River Place Blvd. Austin, TX 78726-9000 www.3M.com/electrical

Litho in USA © 3M 2004 78-8125-9668-8-B