

- Home
- AboutAbhatron
- Products
- LocateDistributoror
- Contact Us
- Request
 Information
- Site Map

Patch Cords

- Jumpers are common universal connection devices for measurement or testing. These connectors will offer solid, semi-permanent connections between instruments with a maximum of safety and reliability. They are however, electrically noisy and may be unsafe at power voltage levels and should only be used for temporary connections. The preferred technique is to use a jumper with a connector matching the post jack or other terminal to which it is desired to connect.
- Please note that figures K,L,M and N are offered with an insulated handle(not shown).
- All patch cords shown here are supplied as either a pair(one red, one black) or individually in red(-102) or black(-103). Add color as suffix to part number.

Patch Cords photo

PART NO.	FIG.	LENGTH INCHES	VVIRE	INSULATIO N	UNIT
1332	А	48	#18 AWG	PVC	Pair
1596-12-	В	12	#18 AWG	PVC	One
1596-24-	В	24	#18 AWG	PVC	One
1596-36-	В	36	#18 AWG	PVC	One
1596-48-	В	48	#18 AWG	PVC	One
1596-60-	В	60	#18 AWG	PVC	One
629	В	12	#20 AWG	Rubber	Pair
657	В	24	#20 AWG	Rubber	Pair
658	В	36	#20 AWG	Rubber	Pair
659	В	48	#20 AWG	Rubber	Pair
1866-12-	C	12	#18 AWG	PVC	One
1866-24-	C	24	#18 AWG	PVC	One
1866-36-	C	36	#18 AWG	PVC	One
1866-48-	C	48	#18 AWG	PVC	One
1866-60-	C	60	#18 AWG	PVC	One
1867-12-	٥	12	#18 AWG	PVC	One
1867-24-	٥	24	#18 AWG	PVC	One
1867-36-	٥	36	#18 AWG	PVC	One
1867-48-	٥	48	#18 AWG	PVC	One
1867-60-	D	60	#18 AWG	PVC	One
649	Е	48	#20 AWG	Rubber	Pair
1865-12-	F	12	#18 AWG	PVC	One
1865-24-	F	24	#18 AWG	PVC	One
1865_36_	F	36	#18 A\/\\G	PVC	One

649	E	48	#20 AVVG	Rubber	Pair
1865-12-	F	12	#18 AWG	PVC	One
1865-24-	F	24	#18 AWG	PVC	One
1865-36-	F	36	#18 AWG	PVC	One
1865-48-	F	48	#18 AWG	PVC	One
1865-60-	F	60	#18 AWG	PVC	One
1510-8-	G	8	#18 AWG	PVC	One
1510-12-	G	12	#18 AVVG	PVC	One
1510-24-	G	24	#18 AVVG	PVC	One
1510-36-	G	36	#18 AVVG	PVC	One
1595-8-	Н	8	#18 AVVG	PVC	One
1595-12-	Н	12	#18 AWG	PVC	One
1595-24-	Н	24	#18 AWG	PVC	One
1595-36-	Н	36	#18 AVVG	PVC	One
1864-12-	J	12	#18 AVVG	PVC	One
1864-24-	J	24	#18 AWG	PVC	One
1864-36-	J	36	#18 AWG	PVC	One
1864-48-	J	48	#18 AWG	PVC	One
1864-60-	J	60	#18 AWG	PVC	One
627	K	48	#20 AVVG	Rubber	Pair
628	L	48	#20 AVVG	Rubber	Pair
647	М	48	#20 AWG	Rubber	Pair
604	Z	12	#20 AWG	Rubber	Pair
605	Z	24	#20 AWG	Rubber	Pair
606	N	36	#20 AWG	Rubber	Pair
607	N	48	#20 AWG	Rubber	Pair
671	0	48	#20 AWG	Rubber	Pair
675	Р	48	#20 AWG	Rubber	Pair
648	Q	48	#20 AWG	Rubber	Pair
1334-8-	R	8	#18 AVVG	PVC	One
1334-12-	R	12	#18 AWG	PVC	One
1334-24-	R	24	#18 AWG	PVC	One
1334-36-	R	36	#18 AVVG	PVC	One
1336-8-	S	8	#18 AWG	PVC	One
1336-12-	S	12	#18 AWG	PVC	One
1336-24-	S	24	#18 AWG	PVC	One
1336-36-	S	36	#18 AWG	PVC	One
1335-8-	T	8	#18 AWG	PVC	One
1335-12-	T	12	#18 AWG	PVC	One
1335-24-	T	24	#18 AWG	PVC	One
1335-36-	T	36	#18 AWG	PVC	One
AWG RATINGS					

AWG				RATINGS	
WIRE	INSULATION	O.D.	STRAND	VOLTAGE	CURRENT
#18	PVC	0.140"	65/36	10KV	10 AMP
#18	Rubber (Buna N)	0.140"	65/36	10KV	10 AMP
#20	Rubber	0.120"	26/34	5KV	8 AMP
#24	PVC	0.090"	19/36	5KV	5 AMP