



Home

About CML

Service

Media Center

Contact


Access CML

PRODUCTS

Products

Based LEDs

CML IT Based LEDs are an effective alternative for based incandescent lamps. Based LEDs have a number of advantages when compared to miniature lamps. Features include a long life expectancy of up to 100,000 hours with low power consumption. Based LEDs are shock and vibration proof and come in a wide variety of colors, styles and voltages.



Part Number: 18626231 Serial Number: 18626

Based LED type: MegaStarLED

Size (inch): T-3 1/4 **Size (mm):** T10


Housing Size: 10x25mm


Base: BA9s Chip number: 3 Chip color: green Wavelength (mA): 525 Op. voltage (V): 230 Rectifier: Half Wave AC current: 3 DC current: -

Type Iv DC current: 450 Voltage tolerance (%): 10%

Op. temperature (°C): $-20~^{\circ}\text{C}$ - $+60~^{\circ}\text{C}$ Storage temperature (°C): $-25~^{\circ}\text{C}$ - $+80~^{\circ}\text{C}$

RoHS Status: Yes





Lampensockel nach DIN EN 60061-1: BA9s / Lamp base in accordance to DIN EN 60061-1: BA9s

Elektrische und optische Daten sind bei einer Umgebungstemperatur von 25°C gemessen. Electrical and optical data are measured at an ambient temperature of 25°C.

Bestell-Nr. Part No.	Farbe Colour	Spannung Voltage	Strom Current	Lichtstärke Lumi. Intensity	Dom. Wellenlänge Dom. Wavelength
18626230	Red	230V AC	3mA	3 x 120mcd	630nm
18626231	Green	230V AC	3mA	3 x 450mcd	525nm
18626232	Yellow	230V AC	3mA	3 x 110mcd	587nm
18626237	Blue	230V AC	3mA	3 x 200mcd	470nm
1862623W3	White Clear	230V AC	3mA	3 x 300mcd	x = 0,31 / y = 0,32
1862623W3D	White Diffuse	230V AC	3mA	3 x 150mcd	x = 0,31 / y = 0,32

Lichtstärkedaten der verwendeten Leuchtdioden bei DC / Luminous intensity data of the used LEDs at DC

Lagertemperatur / Storage temperature -25°C - +80°C
Umgebungstemperatur / Ambient temperature -20°C - +60°C
Spannungstoleranz / Voltage tolerance +10%

Allgemeiner Hinweis: Bedingt durch die Fertigungstoleranzen der Leuchtdioden kann es zu geringfügigen

Schwankungen der Farbe (Farbtemperatur) kommen.

Es kann deshalb nicht ausgeschlossen werden, daß die Farben der Leuchtdioden eines

Fertigungsloses unterschiedlich wahrgenommen werden.

General: Due to production tolerances, colour temperature variations may be detected within

individual consignments.

CML Technologies GmbH & Co. KG D-67098 Bad Dürkheim (formerly EBT Optronic)			Mega StarLEDs T3 ¼ (10x25mm) BA9s				
					Drawn: J.J.	Ch'd: D.L.	Date: 02.11.04
	Revision;		Date:	Name:	Scale: 1,5:1	Datasheet: 1862623xxx	