

---

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

---

Part Number: 531  
Page 1 of 2 Pages

Issue: 3  
Issue Date: 1/10/2006  
Effective Date: 1/30/2006

---


**A. Cordage Construction**

- 1) Conductor
  - a) Material Bare Copper, per ASTM B-3
  - b) AWG, Stranding 18 (41/34) AWG; Finer stranding may be used.
- 2) Insulation
  - a) Material PVC
  - b) Nominal Diameter 0.107
- 3) Core Assembly
  - a) Number of Conductors 3
  - b) Color Code Black, White & Green or Green/Yellow.  
*[Note: The stripe of the Green/Yellow insulation shall be 50% +/- 20%.]*
  - c) Fillers Optional
  - d) Separator Tissue Paper
- 4) Jacket
  - a) Material PVC
  - b) Surface Finish Smooth, non-striated
  - c) Nominal Diameter 0.330
  - d) Color Black
  - e) UL, CSA Type SJT, Minimum\*\*
  - f) Jacket Marking Per UL Standard 62 and CSA C22.2 No. 49.

\*\* Cordage Types with a UL/CSA rating greater than Type SJT may be substituted,

**B. Cord Configuration**

- 1) End 1 Molded Vinyl Grounding Plug, NEMA 5-15P
- 2) End 2 Molded Vinyl Grounding Connector, IEC 320-C13
- 3) Mold Color Black
- 4) Overall Length 79" +/- 2"



Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

---

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

---

**Part Number: 531**  
**Page 2 of 2 Pages**

**Issue: 3**  
**Issue Date: 1/10/2006**  
**Effective Date: 1/30/2006**

---

**C. Industry Approvals and Ratings**

- |                       |                           |
|-----------------------|---------------------------|
| 1) UL                 | UL Standard 62 & 817      |
| 2) CSA                | CSA C22.2 No. 21 & No. 49 |
| 3) Cord Set Rating    | 1250 Watts 10A-125V       |
| 4) Temperature Rating | 60°C, Minimum             |

**D. Packaging**

- |                     |                            |
|---------------------|----------------------------|
| 1) Standard Package | 25 Pieces, Hanked and Tied |
|---------------------|----------------------------|

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.