

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

**Part Number: 6368**  
**Page 1 of 2 Pages**

**Issue: 4**  
**Issue Date: 9/9/2008**  
**Effective Date: 9/9/2008**

**A. Construction**

**Diameters**

- 1) Component 1                                    10 X 1 PAIR
  - a) Conductor                                    24 (7/32) AWG TC
  - b) Insulation                                    0.010" Wall, Nom. PVC, Semi Rigid                                    0.044
  - (1) Color Code                                Alpha Wire Company Color Code M
  
- 2) Cable Assembly                                10 Components Cabled
  - a) Twists:                                        2.8 Twists/foot (min)
- 3) Shield:                                         Alum/Mylar Tape, 25% Overlap, Min.
  - a) Foil Direction                                Foil Facing Out
  - b) Drain Wire                                    24 (7/32) AWG TC
  - c) Braid    TC,65% Coverage, Min.
- 4) Jacket    0.032" Wall, Nom.,PVC                                    0.379 (0.400 Max.)
  - a) Color(s)                                        Gray, Black
  - b) Print    ALPHA WIRE-\* P/N 6368 10PR 24 AWG  
SHIELDED 75C (UL) TYPE CM OR AWM 2464 --- LLXXXXXX  
CSA TYPE CMG FT4    ROHS  
\* = Factory Code

Pair	Color	Pair	Color	Pair	Color
1	BLUE/WHITE - WHITE/BLUE	5	SLATE/WHITE - WHITE/SLATE	9	BROWN/RED - RED/BROWN
2	ORANGE/WHITE - WHITE/ORANGE	6	BLUE/RED - RED/BLUE	10	SLATE/RED - RED/SLATE
3	GREEN/WHITE - WHITE/GREEN	7	ORANGE/RED - RED/ORANGE		
4	BROWN/WHITE - WHITE/BROWN	8	GREEN/RED - RED/GREEN		

*[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]*

**B. Industry Approvals**

- 1) UL    AWM/STYLE2464                                    80°C / 300V  
CM    75°C  
VW-1
- 2) CSA International                            CMG    60°C  
FT4
- 3) EU Directive 2002/95/EC(RoHS):  
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
- 4) California Proposition 65:                The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

**C. Physical & Mechanical Properties**

- 1) Temperature Range                         -20 to 80°C
- 2) Bend Radius                                   10X Cable Diameter
- 3) Pull Tension                                   79 Lbs, Maximum

**D. Electrical Properties**

(For Engineering purposes only)

- 1) Voltage Rating                                300 V<sub>RMS</sub>
- 2) Characteristic Impedance                 75 Ω
- 3) Mutual Capacitance                        30 pf/ft @1 kHz, Nominal
- 4) Ground Capacitance                        50 pf/ft @1 kHz, Nominal
- 5) Conductor DCR                                26 Ω/1000ft @20°C, Nominal
- 6) OA Shield DCR                                3.3 Ω/1000ft @20°C, Nominal

**E. Other**

- 1) Packaging
  - a) 1000 FT
  - b) 500 FT
  - c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

**ALPHA WIRE COMPANY  
CUSTOMER PRODUCT SPECIFICATION**

**Part Number: 6368**  
**Page 2 of 2 Pages**

**Issue: 4**  
**Issue Date: 9/9/2008**  
**Effective Date: 9/9/2008**

- 2) Notes:  
a) Black color jacket is a special request item.

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.  
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.