

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6399
Page 1 of 2 Pages

Issue: 3
Issue Date: 5/26/2005
Effective Date: 8/1/2005

A. Construction

Diameters

- 1) Component 1 25 X 1 PAIR
 - a) Conductor 28 (7/36) AWG TC
 - b) Insulation 0.010" Wall, Nom. Polyethylene(PE) 0.035
 - (1) Color Code Alpha Wire Color Code K

Pair	Color	Pair	Color	Pair	Color
1	BLACK-RED	10	RED-BLUE	19	WHITE-BLUE
2	BLACK-WHITE	11	RED-YELLOW	20	WHITE-YELLOW
3	BLACK-GREEN	12	RED-BROWN	21	WHITE-BROWN
4	BLACK-BLUE	13	RED-ORANGE	22	WHITE-ORANGE
5	BLACK-YELLOW	14	GREEN-WHITE	23	BLUE-YELLOW
6	BLACK-BROWN	15	GREEN-BLUE	24	BLUE-BROWN
7	BLACK-ORANGE	16	GREEN-YELLOW	25	BLUE-ORANGE
8	RED-WHITE	17	GREEN-BROWN		
9	RED-GREEN	18	GREEN-ORANGE		

- c) Pair 2/Cond Cabled Together
 - (1) Twists: 12.0 Twists/foot (min)
- 2) Cable Assembly 25 Components Cabled
 - a) Twists: 2.4 Twists/foot (min)
- 3) Shield: Alum/Mylar Tape, 25% Overlap, Min.
 - a) Foil Direction Foil Facing Out
 - b) Drain Wire 28 (7/36) AWG TC
 - c) Braid TC,90% Coverage, Min.
- 4) Jacket 0.035" Wall, Nom.,PVC 0.440 (0.468 Max.)
 - a) Color(s) GRAY
 - b) Print ALPHA WIRE-* P/N 6399 25PR 28 AWG
SHIELDED 75C (UL) TYPE CL2 OR AWM 2960
LLXXXXXX CSA TYPE CMH FT1 ROHS
* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL AWM/STYLE2960 60°C / 30V
CL2 75°C
VW-1
- 2) CSA International CMH 60°C
FT1
- 3) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
- 4) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 75°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 80 Lbs, Maximum

D. Electrical Properties (For Engineering purposes only)

- 1) Voltage Rating 300 V_{RMS}
- 2) Characteristic Impedance 100 Ω
- 3) Mutual Capacitance 15.5 pf/ft @1 kHz, Nominal
- 4) Ground Capacitance 27.5 pf/ft @1 kHz, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6399
Page 2 of 2 Pages

Issue: 3
Issue Date: 5/26/2005
Effective Date: 8/1/2005

- 5) Conductor DCR 67 Ω /1000ft @20°C, Nominal
- 6) OA Shield DCR 2.2 Ω /1000ft @20°C, Nominal

E. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.