## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 9803C Issue: 3

Page 1 of 2 Pages Issue Date: 4/26/2006 Effective Date: 6/15/2006

A. Construction <u>Diameters</u>

b) Insulation 0.057" Wall, Nom. Polyethylene, Foam 0.144

(1) Color(s)

 Cond
 Color
 Cond
 Color

 1
 NATURAL
 Color
 Cond

2) Shield BC BRAID Shield,95% Coverage, Min.

Jacket 0.035" Wall, Nom., Type I PVC 0.242+/- 0.006

a) Color(s) BLACK

b) Print ALPHA WIRE-\* P/N 9803C 1C 22 AWG

RG 59/U TYPE SHIELDED (UL) TYPE CL2 OR AWM 1354

LLXXXXXX CSA TYPE CMG FT4 ROHS

\* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

**B. Industry Approvals** 

 1) UL
 AWM/STYLE1354
 60°C / 30V

 CL2
 60°C

 2) CSA International
 CMG
 60°C

FT4

3) Military MIL-C-17/RG 59/U type

4) EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

5) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

## C. Physical & Mechanical Properties

1) Temperature Range -20 to 60°C

2) Bend Radius3) Pull Tension10X Cable Diameter12.8 Lbs, Maximum

**D. Electrical Properties** (For Engineering purposes only)

1) Voltage Rating 300  $V_{RMS}$  2) Characteristic Impedance 75  $\Omega$  +/- 3

3) Ground Capacitance 17.3 pf/ft @1 kHz, Nominal

4) Velocity of Propagation 78 %

5) Conductor DCR 15.1  $\Omega$ /1000ft @20°C, Nominal 2.6  $\Omega$ /1000ft @20°C, Nominal

7) Voltage Withstanding 5 kV, Minimum

8) SRL 18 db, Minimum, 5 – 300 Mhz

9) Attenuation, Max dB/100ft 2.3 @ 50 MHz

3.2 @ 100 MHz 4.7 @ 200 MHz 6.8 @ 400 MHz 11.2 @ 1 GHz

## E. Other

Packaging

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 9803C Issue: 3

Page 2 of 2 Pages Issue Date: 4/26/2006 Effective Date: 6/15/2006

a) 1000 FT

b) 500 FT

c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.