


# Super Vu-Tron® III Types SJOOW/SOOW

## 105°C 300 and 600 Volt UL/CSA Portable Cord



### TYPE SJOOW – 300 VOLT – UL/CSA

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOM. INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS†	APPROX. NET WEIGHT LBS/M <sup>(®)</sup>	STD. CTN.
				INCHES	mm	INCHES	mm			
02001	2	18	41/34	0.030	0.76	0.310	8.00	10	56	1000'
02002	3	18	41/34	0.030	0.76	0.320	8.12	10	65	1000'
02003*	4	18	41/34	0.030	0.76	0.345	8.76	7	80	250'
02004	2	16	65/34	0.030	0.76	0.315	8.00	13	68	1000'
02005	3	16	65/34	0.030	0.76	0.335	8.51	13	80	250'
02006	4	16	65/34	0.030	0.76	0.370	9.40	10	95	250'
02007*	2	14	41/30	0.030	0.76	0.370	9.40	18	90	250'
02008	3	14	41/30	0.030	0.76	0.375	9.52	18	110	250'
02009	4	14	41/30	0.030	0.76	0.405	10.29	15	130	250'

### TYPE SOOW – 600 VOLT – UL/CSA

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOM. INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS†	APPROX. NET WEIGHT LBS/M <sup>(®)</sup>	STD. CTN.
				INCHES	mm	INCHES	mm			
02031*	2	18	41/34	0.030	0.76	0.365	9.27	10	75	250'
02032	3	18	41/34	0.030	0.76	0.375	9.53	10	80	250'
02033*	4	18	41/34	0.030	0.76	0.400	10.16	7	110	250'
02034	2	16	65/34	0.030	0.76	0.370	9.40	13	75	250'
02035	3	16	65/34	0.030	0.76	0.395	10.80	13	100	250'
02036	4	16	65/34	0.030	0.76	0.425	10.80	10	120	250'
02021*	5	16	65/34	0.030	0.76	0.515	13.08	8	150	250'
02037*	2	14	41/30	0.045	1.14	0.510	12.95	18	155	250'
02038	3	14	41/30	0.045	1.14	0.525	13.34	18	165	250'
02039	4	14	41/30	0.045	1.14	0.575	14.61	15	215	250'
02022*	5	14	41/30	0.045	1.14	0.675	17.15	12	285	250'
02041*	2	12	65/30	0.045	1.14	0.590	14.99	25	200	250'
02042	3	12	65/30	0.045	1.14	0.600	15.24	25	250	250'
02043	4	12	65/30	0.045	1.14	0.650	16.51	20	280	250'
02023*	5	12	65/30	0.045	1.14	0.730	18.54	16	315	250'
02045	3	10	104/30	0.045	1.14	0.660	16.76	30	320	250'
02046	4	10	104/30	0.045	1.14	0.710	18.03	25	375	250'
02024*	5	10	104/30	0.045	1.14	0.770	19.56	20	432	250'

\* Non-stock item; minimum quantity purchase required.

† Green conductor for grounding only.

® Actual shipping weight may vary.

### Product Construction:

#### Conductors:

- 18 through 10 AWG fully annealed stranded bare copper per ASTM B-174

#### Insulation:

- Premium-grade, color-coded, oil-resistant 105°C EPDM
- Color Code: See chart below

#### Jacket:

- Super Vu-Tron® III, Yellow
- Temperature Range: -50°C to +105°C UL/CSA
- Voltage rating: 300 volts Type SJOOW, 600 volts Type SOOW

#### Jacket Marking:

- CAROL SUPER VU-TRON III (SIZE) 105C (UL) WATER RESISTANT SJOOW (OR SOOW) CSA (-50C) FT-1 P-123-103 MSHA 300 (OR 600) VOLT

### Applications:

- Machine tools
- Power tools
- Dockside power applications
- Motor leads
- Portable machinery
- Cranes
- Submersible pumps

### Features:

- Excellent flexibility in cold temperatures
- Last longer in flex applications
- Integral Flexfill®
- Ozone- and weather-resistant
- UL Listed and CSA Certified for indoor and outdoor use
- Water-resistant
- Safety-colored
- High heat and flame resistance
- Resistant to oils, acids and chemicals
- Excellent abrasion and cut resistance

### Industry Approvals:

- UL Flexible Cord - UL Subject 62
- CSA Flexible Cord - C22.2-49
- MSHA Approved
- RoHS Compliant

### Packaging:

- 250' (76.2 m), 500' (152.4 m) and 1000' (304.8 m) reels
- Other put-ups available on special order

### COLOR CODE CHART

NO. OF CONDUCTORS	COLOR
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Orange, Green

**CAROL BRAND**

**UL LISTED**

**CSA**

**MSHA**  
Mine Safety and Health Administration

**RoHS Compliant**  
Directive 2002/95/EC

**General Cable**