

Rack PDU, Basic, 1U, 16A, 208&230V, (12)C13

APC Basic Rack PDU , Input: 120V, 208V, 230V , Input Connections: IEC-320 C20 , Cord Length: 8 feet (2.50 cm) , Output: 120V, 208V, 230V , Output Connections: IEC 320 C13

Includes: Rack Mounting Brackets, User Manual

Part Number : **AP9553**

DISCONTINUED : recommended replacement product [AP9565](#)

[Contact Sales](#)



- [Compare Models](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



[\[+\] More Images](#)

Technical Specifications

Output

Nominal Output Voltage	120V,208V,230V
Maximum Total Current Draw per Phase	16A

Output Connections (12) IEC 320 C13



Always on Outlets	12
Overload Protection	Yes

Features:

- o 19 inch Rack-Mountable
- o Low Cost Power Distribution

Input

Nominal Input Voltage	120V,208V,230V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	8.20 feet (2.50 meters)
Acceptable Input Voltage	90-253 VAC
Maximum Line Current per phase	16A
Maximum Input Current per phase	16A
Load Capacity	3680 VA
Overload Capacity (at nominal rated input V)	20

Physical

Net Weight	3.00 lbs. (1.36 kg)
Maximum Height	1.75 inches (44 mm)
Maximum Width	17.00 inches (432 mm)
Maximum depth	4.00 inches (102 mm)
Shipping Weight	5.40 lbs. (2.45 kg)
Shipping Height	2.75 inches (70 mm)
Shipping Width	19.00 inches (483 mm)
Shipping Depth	13.50 inches (343 mm)
Color	Black
Units per Pallet	100.00

Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CE,EN 60950,UL 1950,UL Listed,cUL Listed, VDE
Standard Warranty	2 years repair or replace

Copyright © American Power Conversion Corp., all rights reserved

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)