

Basic Rack PDU

Rack PDU, Basic, 1U, 30A, 208V, (12) C13



APC Basic Rack PDU , Input: 208V , Input Connections: NEMA L6-30P , Cord Length: 12 feet (3.66 meters) , Output: 208V , Output Connections: IEC 320 C13

Includes: Installation guide, Rack Mounting brackets, User Manual



Standard Lead Time: Usually in Stock


AP9571 Features

Resettable circuit breakers	Enables a quick recovery from overload events.
Vertical mounting capability	
Horizontal mounting capability	
Single-branch power input	


Basic Rack PDU Features & Benefits

Agility	
Rack-Mountable	Includes horizontal, vertical, and toolless-mount varieties. Puts power where it is needed most - in the racks near the equipment.
Single input power source	Supply power from one branch whip to multiple pieces of equipment, conveniently powering rack-mount equipment. Saves time and money during installation by using one branch whip and standard connections.
Wide range of input and output connections	Product family includes a variety of input and output connections to distribute 120V, 208V, or 230V power to multiple outlets. Having a variety of inputs and outputs allow users to adapt to varying power requirements. APC offers units that bring up to 14.4kW using a single branch whip.

Output

Nominal Output Voltage	208V	
Maximum Total Current Draw per Phase	24A	
Output Connections	(12) IEC 320 C13	
Always on Outlets	12	
Overload Protection	Yes	

Input

Nominal Input Voltage	208V	
Input Frequency	50/60 Hz	
Regulatory Derated Input Current (North America)	24A	
Input Connections	NEMA L6-30P	
Cord Length	12 feet (3.66 meters)	
Number of Power Cords	1	
Acceptable Input Voltage	200-240 VAC	
Maximum Line Current per phase	30A	
Maximum Input Current per phase	30A	
Load Capacity	4992 VA	

Physical

Net Weight	5.60 lbs. (2.55 kg)
Maximum Height	1.70 inches (43 mm)
Maximum Width	17.50 inches (445 mm)
Maximum Depth	2.50 inches (64 mm)
Shipping Weight	8.00 lbs. (3.64 kg)
Shipping Height	6.00 inches (152 mm)
Shipping Width	19.12 inches (486 mm)
Shipping Depth	6.95 inches (177 mm)
Color	Black

Environmental

Operating Environment	5 - 113 °F (-15 - 45 °C)
Operating Relative Humidity	5%
Operating Elevation	0-15000 feet (0-4500 meters)
Storage Temperature	-13 - 149 °F (-25 - 65 °C)
Storage Relative Humidity	5%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	cUL Listed,CSA,UL 60950,UL Listed
Standard Warranty	2 years repair or replace
ROHS/WEEE Compliance	RoHS 7b Exemption