



Select Your Country/Region

[Search](#)  
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

## Relay I/O SmartSlot Card

Control and monitor power through a dry-contact interface.

Includes: User Manual

Part Number : **AP9610**

- [Compare Models](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

### Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



## Technical Specifications

### Physical

Net Weight	0.30 lbs. ( 0.14 kg)
Maximum Height	1.50 inches ( 38 mm)
Maximum Width	4.75 inches (121 mm)
Maximum depth	4.25 inches (108 mm)
Shipping Weight	1.00 lbs. ( 0.45 kg)
Shipping Height	2.86 inches ( 73 mm)
Shipping Width	6.50 inches (165 mm)
Shipping Depth	9.00 inches (229 mm)
Color	Black
Units per Pallet	672.00

### Features:

- Dry Contact inputs

### Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Storage Temperature	-15 - 65 °C (5 - 149 °F)
Operating Relative Humidity	0 - 95%
Storage Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Elevation	0-50000 feet (0-15000 meters)

## Conformance

Regulatory Approvals

C-tick,CE,DOC/Industry Canada,EN 55022  
Class B,EN 55024,EN 55082,FCC Part 15 Class  
B,VCCI

---

Standard Warranty

2 years repair or replace

---

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)