

AR100HD

[NetShelter WX Enclosures](#)

NetShelter WX 13U w/Threaded Hole Vertical Mounting Rail Vented Front Door Black

Wall-mounted rack enclosures for networking applications in IT environments.

Includes: Key(s), User Manual, Wall-mounting template

Standard Lead Time: Usually in Stock



Physical

Net Weight	42.73 KG
Maximum Height	654.00 mm
Maximum Width	584.00 mm
Maximum Depth	622.00 mm
Shipping Weight	52.27 KG
Shipping Height	838.00 mm
Shipping Width	686.00 mm
Shipping Depth	775.00 mm
Weight Capacity (static load)	90.91 KG
Minimum Mounting Depth	240.00 mm
Rack Height	13U
Color	Black

Conformance

Standard Warranty	5 year repair or replace
Standards	EIA-310-D
Protection Class	IP 20

AR100HD Features

Adjustable mounting depth	Vertical mounting rails are adjustable for equipment with various mounting depths.
Ships fully assembled	NetShelter VX Enclosures ship fully assembled reducing the time required to install equipment.
Adjustable Front Vertical Mounting Rail	The front mounting rails can be adjusted to allow for various mounting depths and to allow for additional clearance from the front door.
Doors open 180 degrees	Two people are often required to stand in front of an enclosure on opposite sides to install heavy rack-mount equipment. A door that opens 180 degrees allows for installation of equipment without the need to remove the door making installation fast and easy.
Powder coat paint finish	

NetShelter WX Enclosures Features & Benefits

Convenience	
Wall-mountable	Four "key hole" slots spaced 16" apart on the rear door allow the enclosure to mount directly to building walls. A template is provided to assist in locating the proper hole placement.
Multi-purpose mounting rails	NetShelter WX Enclosures ships with the front vertical mounting rails oriented such that #12-24 tapped holes are useable for mounting equipment. The front rails are also field-reversible to provide square mounting holes for use with caged nuts.
Adjustable front rail	The front mounting rails can be adjusted to allow for various mounting depths and to allow for additional clearance from the front door.
Labeled U positions	APC has eliminated the pain involved in determining where to install rack-mount devices within an enclosure by labeling each vertical mounting rail with the actual U positions.
Unit symmetry	Left or right hand door swing operation can be obtained depending on orientation selected upon installation.
Integrated cable access holes	Eight 2-inch cable access holes are located at the top, sides, and bottom of the rear door for ample cabling provisions. Grommets and caps are included.
Rubber feet	Four rubber feet are provided for optional floor mounting.
Serviceability	
Double-hinged design	Provides front and rear access to installed equipment.
Availability	
Ventilated	Front Doors and Side Panels are perforated to provide ventilation for components typically installed. Fully ventilated and partially ventilated front doors are available.
Protection	
Lockable Doors	All NetShelter WX Enclosures include key lockable front doors to prevented unwanted access.