

Select Your Country/Region

Search

HomeProductsSupportServicesSelectorsHow to Buy

NetShelter VX 47U Enclosure w/Sides Black

Rack enclosures with advanced cooling, power distribution, and cable management for server and networking applications in IT environments.

Includes: Casters, Doors, Key(s), Leveling feet, Roof, Side Panels, User Manual

Part Number : AR2103BLK

<u>Compare Models</u>

<u>■ Compare Models</u>

<u>■ Email Technical Specifications</u>

<u>■ Printer Friendly</u>

Additional Information Product Overview

<u>User Manual & Installation Guides</u> <u>Submittal Drawings</u> <u>Product Distribution</u>

Technical Specifications

DPhysical

Net Weight	386.00 lbs. (175.45 kg)
Maximum Height	90.25 inches (2292 mm)
Maximum Width	23.50 inches (597 mm)
Maximum depth	42.20 inches (1072 mm)
Shipping Weight	438.00 lbs. (199.09 kg)
Shipping Height	96.00 inches (2438 mm)
Shipping Width	29.50 inches (749 mm)
Shipping Depth	47.50 inches (1207 mm)
Weight Capacity (static load)	2000.00 lbs. (909.09 kg)
Weight Capacity (dynamic load)	2000.00 lbs. (909.09 kg)
Rack Height	47U
Color	Black
Units per Pallet	1.00
Vertical Posts	16 gauge
Front Door	16 gauge
Rear Door	16 gauge
Roof	18 gauge
EIA Mounting Rails	14 gauge
Side Panels	20 gauge



Standard Warranty

5 year repair or replace





[+] More Images

Options:

- o AC Connections
- O Baying Kits
- O Services

Features:

- O Adjustable mounting depth
- Guaranteed Compatability
- O Lockable doors and side panels
- O Multi-vendor equipment compatibility
- Numbered U positions
- O Optimized depth
- O Optimized width
- O Powder coat paint finish
- Protective grounding provisions
- O Quick release doors
- Quick release side panels
- Rear Cable Management channels
- Reversible doors
- O Roof and base cable access
- Ships fully assembled
- Split rear doors
- UBC Zone 4 stabilization provisions

Standards	EIA-310-D
Protection Class	IP 20

<u>Copyright</u> © American Power Conversion Corp., all rights reserved <u>About APCInvestorsJob SeekersPressFeedbackContactPrivacy Policy</u>