
 Select Your Country/Region 

[Search](#)
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)


NetShelter VX 750mm Wide 42U Enclosure w/Sides Black

Rack enclosures with advanced cooling, power distribution, and cable management for server and networking applications in IT environments.

Includes: Casters, Doors, Key(s), Leveling feet, Roof, Side Panels, User Manual

Part Number : **AR2310BLK**



-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)

Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Submittal Drawings](#)
- [Product Distribution](#)



[+] More Images

Technical Specifications

Physical

Net Weight	372.00 lbs. (169.09 kg)
Maximum Height	81.50 inches (2070 mm)
Maximum Width	29.50 inches (749 mm)
Maximum depth	42.20 inches (1072 mm)
Shipping Weight	427.00 lbs. (194.09 kg)
Shipping Height	87.00 inches (2210 mm)
Shipping Width	35.50 inches (902 mm)
Shipping Depth	47.50 inches (1207 mm)
Weight Capacity (static load)	2000.00 lbs. (909.09 kg)
Weight Capacity (dynamic load)	2000.00 lbs. (909.09 kg)
Rack Height	42U
Color	Black
Units per Pallet	1.00
Vertical Posts	16 gauge
Front Door	16 gauge
Rear Door	16 gauge
Roof	18 gauge
EIA Mounting Rails	14 gauge
Side Panels	20 gauge

Conformance

Standard Warranty	5 year repair or replace
-------------------	--------------------------

Options:

- [AC Connections](#)
- [Baying Kits](#)
- [Services](#)

Features:

- Adjustable mounting depth
- Facilitates rear/vertical cable management
- Facilitates side cable management
- Guaranteed Compatibility
- Lockable doors and side panels
- Mounting provisions for vertical power distribution
- Multi-vendor equipment compatibility
- Numbered U positions
- Optimized depth
- Powder coat paint finish
- Protective grounding provisions
- Quick release doors
- Quick release side panels
- Rear Cable Management channels
- Removeable doors and side panels
- Reversible doors
- Rolls through a 7 foot doorway
- Roof and base cable access
- Ships fully assembled
- Split rear doors
- UBC Zone 4 stabilization provisions
- Vertical Mounting Rails with square holes
- Wide form factor (29.5"/750mm)

Standards

EIA-310-D

Protection Class

IP 20

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)