

Line-R 1200VA Automatic Voltage Regulator

Automatic voltage regulation for protection against brownouts and overvoltages.

Includes: User Manual

Part Number : **LE1200I**

- [Compare Models](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



Technical Specifications

Output

Number of Outlets	4
Receptacle Style	IEC 320-C13

Input

Nominal input voltage	230V
Input frequency	50/60 Hz
Input Connection Type	IEC-320 C14
Maximum Line Current per phase	5.20A
Cord Length	6.50 feet (1.98 meters)

Surge Protection and Filtering

Surge energy rating	300 Joules
EMI/RFI Noise rejection (100 kHz to 10 mHz)	55 dB
Peak Current Common Mode	12 kAmps
Let Through Voltage Rating	< 900

Physical

Net weight	9.24 lbs. (4.20 kg)
Maximum height	4.55 inches (116 mm)
Maximum width	8.43 inches (214 mm)
Maximum depth	5.55 inches (141 mm)
Shipping Weight	9.90 lbs. (4.50 kg)
Shipping Height	6.90 inches (175 mm)
Shipping Width	10.75 inches (273 mm)
Shipping Depth	8.15 inches (207 mm)
Master Carton Units	4.00
Master Carton Dimensions (Length x Width x Height)	16.73 X 10.95 X 14.3 inches
Master Carton Weight	42.00 lbs.
SCC Codes	1073130419793 2
Color	Beige

Environmental

Features:

- o Automatic Voltage Regulation (AVR)
- o Brownout correction
- o Overvoltage Correction
- o Status Indicator LED's
- o Surge Protection

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	5 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	5 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

 **Conformance**

Approvals	C-tick,CE,EN 55024,EN 60950,GOST,GS Mark,PCBC
Standard warranty	2 years repair or replace

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)