

 Select Your Country/Region 




[Search](#)  
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

## APC ESSENTIAL SURGEARREST 7 OUTLET 120V

Essential surge protection for computers and home electronics.

Includes: User Manual

Part Number : **P74**

-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)

### Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)




[+] More Images

## Technical Specifications

### Output

Number of Outlets	7
Receptacle Style	NEMA 5-15R

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Maximum Line Current per phase	15A
Cord Length	4 feet ( 1.22 meters)

### Surge Protection and Filtering

Surge energy rating	490 Joules
eP Joule Rating	1080
EMI/RFI Noise rejection (100 kHz to 10 mHz)	20 dB
Peak Current Normal Mode	10 kAmps
Peak Current Common Mode	30 kAmps
Let Through Voltage Rating	< 330

### Physical

Net Weight	1.00 lbs. ( 0.45 kg)
------------	----------------------

### Features:

- i Building Wiring Fault Indicator
- i Catastrophic Event Protection
- i Fail Safe Mode
- i IEEE let-through rating and UL 1449 compliance
- i Lightning and Surge Protection
- i Noise Filtering
- i Protection Working Indicator
- i Status Indicator LED's
- i Surge Protection
- i Transformer Block Spacing

Maximum Height	12.50 inches (318 mm)
Maximum Width	3.00 inches ( 76 mm)
Maximum depth	1.40 inches ( 36 mm)
Shipping Weight	1.33 lbs. ( 0.60 kg)
Shipping Height	14.50 inches (368 mm)
Shipping Width	5.25 inches (133 mm)
Shipping Depth	1.75 inches ( 44 mm)
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	16.5 X 7.5 X 15 inches
Master Carton Weight	18.52 lbs.
SCC Codes	1073130420073 1
Color	Charcoal
Units per Pallet	768.00

### Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

### Conformance

Regulatory Approvals	CSA,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)