



APC Essential SurgeArrest, 7 outlet, phone line protection, 10 ft power cord

Part Number: P7T10

P7T10

Output

Number of Outlets	7
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (manual switch)
Input Connections	NEMA 5-15P
Maximum Line Current per phase	15A
Cord Length	10 feet (3.05 meters)



Surge Protection and Filtering

Surge energy rating	420 Joules
eP Joule Rating	1080
EMI/RFI Noise rejection (100 kHz to 10 MHz)	55 dB
Peak Current Normal Mode	10 kAmps

Peak Current Common Mode	30 kAmps
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Data Lines Protected (multi-line only)	--
Let Through Voltage Rating	< 330

Physical

Net Weight	1.20 lbs. (0.55 kg)
Maximum Height	14.00 inches (356 mm)
Maximum Width	3.00 inches (76 mm)
Maximum depth	2.00 inches (51 mm)
Shipping Weight	1.80 lbs. (0.82 kg)
Shipping Height	14.00 inches (356 mm)
Shipping Width	5.25 inches (133 mm)
Shipping Depth	1.88 inches (48 mm)
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	16.37 x 15.5 x 8.13 inches (416 x 394 x 207 mm)
Master Carton Weight	20.00 lbs.
SCC Codes	10731304016585
Color	Beige
Units per Pallet	1092.00

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CSA,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$25000
UL 1449 TVSS Rating	330 V

*Estimated Resale Price - Without Tax/VAT