



APC Essential A/V Surge Protector, 8 outlet, phone line (w/splitter) & coax protection

Part Number: P8T3V



Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P
Maximum Line Current per phase	15A
Cord Length	2.44 meters



Surge Protection and Filtering

Surge energy rating	1700 Joules
eP Joule Rating	2525
EMI/RFI Noise rejection (100 kHz to 10 mHz)	70 dB
Peak Current Normal Mode	20 kAmps
Peak Current Common Mode	40 kAmps
Data Line Protection	RJ-11 Modem/Fax/DSL protection (four wire dual line),Cable modem / Video protection
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 85

Physical

Net Weight	1.32 KG
Maximum Height	286.00 mm
Maximum Width	146.00 mm
Maximum Depth	38.00 mm
Shipping Weight	1.41 KG
Shipping Height	382.00 mm
Shipping Width	275.00 mm
Shipping Depth	48.00 mm
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	476 x 289 x 383 mm
Master Carton Weight	17.27 KG
SCC Codes	1073130419989 9
Color	Silver Satin

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330V