



APC Home/Office Surge Protector, 8 outlet, phone line (w/splitter) & coax protection

Part Number: P8VT3




Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	1.83 meters
Input Breaker Capacity	15A



Surge Protection and Filtering

Surge energy rating	1750 Joules
eP Joule Rating	2525
EMI/RFI Noise rejection (100 kHz to 10 mHz)	70 dB
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines),Cable modem / Video protection
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 85

Physical

Net Weight	0.92 KG
Maximum Height	32.00 mm
Maximum Width	89.00 mm
Maximum Depth	330.00 mm
Shipping Weight	1.10 KG
Shipping Height	60.00 mm
Shipping Width	142.00 mm
Shipping Depth	360.00 mm
Master Carton Units	6.00
Master Carton Dimensions (Length x Width x Height)	381 x 203 x 305 mm
Master Carton Weight	7.50 KG
Color	Black

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330V