

APC ProtectNet standalone surge protector for digital phone lines

Part Number: PDIGITEL



Input

Input Connections	--
-------------------	----

Surge Protection and Filtering

Peak Current Normal Mode	0.20 kAmps
Peak Current Common Mode	0.15 kAmps
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ45 ISDN / T1 protection
Data Lines Protected (multi-line only)	1-8
Let Through Voltage Rating	< 60

Physical

Net Weight	0.06 KG
Maximum Height	103.00 mm

Maximum Width	47.00 mm
Maximum Depth	28.00 mm
Shipping Weight	0.14 KG
Shipping Height	104.00 mm
Shipping Width	91.00 mm
Shipping Depth	38.00 mm
Master Carton Units	144.00
Master Carton Weight	13.20 lbs.
SCC Codes	10731304013874
Color	Beige
Units per Pallet	750.00

Environmental

Operating Environment	-15 - 65 °C
Operating Relative Humidity	0%
Storage Temperature	-15 - 65 °C
Storage Relative Humidity	0%

Conformance

Regulatory Approvals	CE,CSA,UL Listed,VDE
Standard Warranty	Lifetime
Environmental Compliance	RoHS

[Copyright](#) © American Power Conversion Corp., all rights reserved