

 Select Your Country/Region 




[Search](#)
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Professional SurgeArrest 8 Outlet 120V

Reliable Surge Protection for Home or Office Computers and Electronic Equipment.

Includes: User Manual

Part Number : **PRO8**

-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)



[+] More Images

Additional Information


- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)

Technical Specifications

Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Maximum Line Current per phase	15A

Surge Protection and Filtering

Surge energy rating	320 Joules
eP Joule Rating	1760
EMI/RFI Noise rejection (100 kHz to 10 mHz)	60 dB
Peak Current Normal Mode	13 kAmps
Peak Current Common Mode	13 kAmps
Dataline protection	--
Data Lines Protected (multi-line only)	--
Let Through Voltage Rating	< 85

Physical

Net Weight	1.90 lbs. (0.86 kg)
Maximum Height	1.75 inches (44 mm)
Maximum Width	8.00 inches (203 mm)

Features:

- i Always on Outlets
- i Catastrophic Event Protection
- i Lightning and Surge Protection
- i Protection working indicator
- i Right Angle Plug
- i Site wiring fault indicator
- i Transformer Block Spacing

Maximum depth	5.75 inches (146 mm)
Shipping Weight	2.30 lbs. (1.05 kg)
Shipping Height	2.00 inches (51 mm)
Shipping Width	12.50 inches (318 mm)
Shipping Depth	6.25 inches (159 mm)
Master Carton Units	12.00
Master Carton Weight	29.50 lbs.
SCC Codes	10731304000812
Color	Beige
Units per Pallet	600.00

Environmental

Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CSA,UL 1283,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)