



APC Smart-UPS 1400VA RM 3U 120V Shipboard

APC Smart-UPS, 1400VA/950W, Input 120V/Output 120V, Interface Port DB-9 RS-232, SmartSlot, Rack Height 3 U

Includes: CD with software, User Manual

Part Number : **SU1400RMX93**

DISCONTINUED : recommended replacement product [SUA1500R2X93](#)

- [Compare Models](#)
- [Runtime Chart](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

Additional Information

- [Product Overview](#)
- [Product Distribution](#)



Technical Specifications

- Output**
- Input**
- Batteries & Runtime**
- Communications & Management**
- Surge Protection and Filtering**
- Physical**
- Environmental**
- Conformance**

Options:

- [Automatic Transfer Switches](#)
- [Interface Connections](#)
- [Management Devices](#)
- [Rack Power Distribution](#)
- [Replacement Battery Cartridges](#)
- [Services](#)
- [Software](#)
- [Step Down Transformers](#)

General Features:

- Adjustable voltage sensitivity
- Adjustable voltage-transfer points
- Audible alarms
- Automatic restart of loads after UPS shutdown
- Automatic self-test
- Boost and Trim Automatic Voltage Regulation (AVR)
- Cold-start capable
- Generator compatible
- Hot-swappable batteries
- Intelligent battery management
- LED status indicators
- Network manageable
- Power conditioning
- Predictive failure notification
- Resettable circuit breakers
- Safety-agency approved
- Serial Connectivity
- SmartSlot
- Temperature-compensated battery charging

[more details...](#)

Topology: Line Interactive

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.

[Copyright © American Power Conversion Corp., all rights reserved](#)

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)