

## Smart-UPS VT

### **APC Smart-UPS VT 10kVA 208V w/3 Batt. Modules Exp. to 4, Start-Up 5X8, Internal Maintenance Bypass**



APC Smart-UPS VT, 8000 Watts / 10 kVA, Input 208V 3PH / Output 120V, 208V, 208V 3PH, Interface Port DB-9 RS-232, Smart-Slot

**Includes:** Battery modules ship installed, Bolt down brackets, CD with software, Installation guide, Power modules ship installed, Smart UPS signalling RS-232 cable, Start up included, User Manual, Web/SNMP Management Card

# Smart-UPS VT Features & Benefits

## Availability

- Dual mains input** Increases availability by allowing the UPS to be connected to two separate power sources.
- Scalable runtime** Allows additional run time to be quickly added as needed.
- Hot-swappable batteries** Ensures clean, uninterrupted power to protected equipment while batteries are being replaced
- Generator Compatible** Ensures clean, uninterrupted power to protected equipment when generator power is used.
- Automatic internal bypass** Supplies utility power to the connected loads in the event of a UPS overload condition or fault.
- Battery modules connected in parallel** Delivers higher availability through redundant batteries.

## Serviceability

- User-replaceable batteries** Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR)
- Battery replacement without tools** Allows quick, easy battery replacement.
- Automatic self-test** Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Shippable with modules installed** Enables pre-installation UPS staging and testing and faster installation.
- Modular design** Provides fast serviceability and reduced maintenance requirements via self-diagnosing, field-replaceable modules.

## Manageability

- Network manageable** Provides remote management of the UPS over the network.
- InfraStruXure Manager Compatible** Enables centralized management via the APC InfraStruXure® Manager.
- LCD display** Alpha-Numeric Display which displays system parameters and alarms.
- Audible Alarms** Provides notification of changing utility power and UPS conditions.
- Programmable frequency** Ensures compatibility with different input frequencies.
- LED status indicators** Quickly understand unit and power status with visual indicators.
- SmartSlot** Customize UPS capabilities with management cards.

## Total Cost of Ownership

- Input power factor correction** Minimizes installation costs by enabling the use of smaller generators and cabling.
- Temperature-compensated battery charging** Prolongs battery life by regulating the charge voltage according to battery temperature.
- Manual maintenance bypass** Reduces installation costs by eliminating the need for an external mechanical bypass.
- Intelligent Battery Management** Maximizes battery performance, life, and reliability through intelligent, precision charging.

## Protection

- Frequency and voltage regulation** Gives higher application availability by correcting poor frequency and voltage conditions without using the battery.
- Safety-agency** Ensures the product has been tested and approved to work safely with the

approved connected service provider equipment and within the specified environment.  
UL, FCC, CE, C-Tick approvals.

Cold-start capable Provides temporary battery power when the utility power is out.

## Output

Output Power Capacity	8000 Watts / 10 kVA
Max Configurable Power	8000 Watts / 10 kVA
Nominal Output Voltage	120V,208V,208V 3PH
Output Voltage Note	Configurable for 208 and 220V - 3 Phase
Efficiency at Full Load	93%
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	57 - 63 Hz for 60 Hz nominal
Crest Factor	Unlimited
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 5-wire (3PH + N + G) (1) Screw Terminals
Bypass	Built-in Maintenance Bypass,Built-in Static Bypass

## Input

Nominal Input Voltage	208V 3PH
Input Frequency	40 - 70 Hz
Input Connections	Hard Wire 5-wire (3PH + N + G)
Input voltage range for main operations	165 - 240V
Other Input Voltages	220
Maximum Input Current	27A
Input Breaker Capacity	35A

## Batteries & Runtime

Battery Type	VRLA
Included Battery Modules	3
Available Battery Slots	1
Typical recharge time	5 hour(s)
Replacement Battery	<a href="#">SYBT4</a>
RBC™ Quantity	3
Typical Backup Time at Half Load	73.5 minutes (4000 Watts)
Typical Backup Time at Full Load	31.0 minutes (8000 Watts)

## Communications & Management

Interface Port(s)	DB-9 RS-232,Smart-Slot
Pre-Installed SmartSlot™ Cards	<a href="#">AP9619</a>
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms : configurable delays
Emergency Power Off (EPO)	Yes

## Physical

Maximum Height	1499.00 mm
Maximum Width	523.00 mm
Maximum Depth	925.00 mm
Net Weight	506.82 KG
Shipping Weight	537.74 KG
Shipping Height	1643.00 mm
Shipping Width	650.00 mm
Shipping Depth	1062.00 mm
Color	Black
Units per Pallet	1.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0%
Operating Elevation	0-999.9 meters
Storage Temperature	-50 - 40 °C
Storage Relative Humidity	0%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	54.00 dBA
Online Thermal Dissipation	2047.00 BTU/hr
Protection Class	NEMA 1

## Conformance

Regulatory Approvals

cUL Listed,ISO 14001,ISO 9001,UL 1778

Standard Warranty

1 year repair or replace,Start-Up Service

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.