

APC Symmetra 4kVA Scalable to 8kVA N+1 208/240V w/Outlets

APC Symmetra, 4000VA/2800W, Input 208V/Output 120V, 208V, Interface Port DB-9 RS-232, SmartSlot

Includes: CD with software, User Manual

Part Number : **SY4KEX-PD**

DISCONTINUED : recommended replacement product [SYA4K8P](#)

[Compare Models](#)

[Runtime Chart](#)

[Email Technical Specifications](#)

[Printer Friendly](#)



Additional Information

[Product Overview](#)

[User Manual & Installation Guides](#)

[Product Distribution](#)

[+] More Images

Technical Specifications

Output

Output power capacity	4000 VA
Output power capacity	2800 Watts
Max Configurable Power	8000 VA
Max Configurable Power	5600 Watts
Nominal output voltage	120V,208V
Output Voltage Note	Configurable for 120/208 or 120/240 output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	57 - 63 Hz for 60 Hz nominal
Crest Factor	up to 5 : 1
Waveform type	Sine wave

(1) Hard Wire 3-wire (2PH + G)
 (1) Hard Wire 4-wire (2PH + N + G)

(2) NEMA 5-15R



Output Connections

(2) NEMA L14-30R



(1) NEMA L6-30R



Options:

- [Automatic Transfer Switches](#)
- [Batteries](#)
- [External BackPlate Kits](#)
- [Interface Connections](#)
- [Management Devices](#)
- [Power Cords](#)
- [Power Modules](#)
- [Rack Power Distribution](#)
- [Service Bypass Panels](#)
- [Services](#)
- [Software](#)
- [Step Down Transformers](#)

General Features:

- [Audible alarms](#)
- [Automatic internal bypass](#)
- [Automatic restart of loads after UPS shutdown](#)
- [Automatic self-test](#)
- [Battery modules connected in parallel](#)
- [Cold-start capable](#)
- [Configurable for N+1 internal redundancy](#)
- [Disconnected battery notification](#)
- [Field-replaceable power distribution panel](#)
- [Frequency and voltage regulation](#)
- [Generator compatible](#)

Input

Bypass	Internal Bypass (Automatic and Manual)
Nominal input voltage	208V
Input frequency	45 - 65 Hz (auto sensing)
Input Connection Type	Hard Wire 3 wire (1PH+1PH+G)
Input voltage range for main operations	155 - 276V
Other Input Voltages	240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery Modules Shipped with Unit	1
Battery Slots Empty	1
Replacement battery cartridge	SYBATT
Typical backup time at half load	16.3 minutes (1400 Watts)
Typical backup time at full load	5.0 minutes (2800 Watts)
Runtime Chart	Symmetra

Communications & Management

Interface port	DB-9 RS-232,SmartSlot
Available Smart Slot Interface Quantity	3
Pre-Installed SmartSlot Cards	AP9617
Control panel	Multi-function LCD status and control console
Audible alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes

Physical

Maximum height	31.00 inches (787 mm)
Maximum width	24.00 inches (610 mm)
Maximum depth	27.00 inches (686 mm)
Net weight	425.00 lbs. (193.18 kg)
Shipping Weight	512.00 lbs. (232.73 kg)
Shipping Height	42.50 inches (1080 mm)
Shipping Width	33.00 inches (838 mm)
Shipping Depth	29.00 inches (737 mm)
Color	Beige

Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)

- i Hot-swappable batteries
 - i Hot-swappable intelligence modules
 - i Hot-swappable power modules
 - i InfraStruXure Manager compatible
 - i Input power factor correction
 - i Intelligent battery management
 - i LCD display
 - i Manageable external batteries
 - i Modular design
 - i Network manageable
 - i Plug-and-Play external batteries
 - i Power conditioning
 - i Power Modules connected in parallel
 - i Predictive failure notification
 - i Programmable frequency
 - i Redundant Intelligence Modules
 - i Resettable circuit breakers
 - i Safety-agency approved
 - i Scalable power capacity
 - i Scalable runtime
 - i SmartSlot
 - i User-replaceable batteries
 - i User-replaceable intelligence modules
 - i User-replaceable power modules
- [more details....](#)

Topology: Double Conversion Online

Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)
Online thermal dissipation	1242 BTU/hr

Conformance

Approvals	CSA,FCC Part 15 Class A,UL 1778
Standard warranty	