

## APC Symmetra RM 12kVA Scalable to 12kVA N+1 or 16kVA 208/240V w/208 to 120V 5kVA Step-Down Transform

APC Symmetra, 12000VA/8400W, Input 208V/Output 120V, 208V, Interface Port DB-9 RS-232, RJ-45 10 Base-T ethernet for web/ SNMP/ Telnet management, SmartSlot, Rack Height 17 U

Includes: CD with software, Rack Mounting Brackets, Rack Mounting support rails, User Manual

Part Number : **SYP12K12RMT-P1**

**DISCONTINUED** : recommended replacement product [SYA12K16RMP](#)

- [Compare Models](#)
- [Runtime Chart](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

### Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)



[\[+\] More Images](#)

## Technical Specifications

- [Output](#)
- [Input](#)
- [Batteries & Runtime](#)
- [Communications & Management](#)
- [Physical](#)
- [Environmental](#)
- [Conformance](#)

### Options:

- [Automatic Transfer Switches](#)
- [Batteries](#)
- [Interface Connections](#)
- [Internal BackPlate Kits](#)
- [Management Devices](#)
- [Power Cords](#)
- [Power Modules](#)
- [Rack Power Distribution](#)
- [Service Bypass Panels](#)
- [Services](#)
- [Software](#)
- [Step Down Transformers](#)

**General Features:**

- o Audible alarms
  - o Automatic internal bypass
  - o Automatic restart of loads after UPS shutdown
  - o Automatic self-test
  - o Battery modules connected in parallel
  - o Cold-start capable
  - o Configurable for N+1 internal redundancy
  - o Disconnected battery notification
  - o Field-replaceable power distribution panel
  - o Frequency and voltage regulation
  - o Generator compatible
  - o Hot-swappable batteries
  - o Hot-swappable intelligence modules
  - o Hot-swappable power modules
  - o InfraStruXure Manager compatible
  - o Input power factor correction
  - o Intelligent battery management
  - o LCD display
  - o Manageable external batteries
  - o Modular design
  - o Network manageable
  - o Plug-and-Play external batteries
  - o Power conditioning
  - o Power Modules connected in parallel
  - o Predictive failure notification
  - o Programmable frequency
  - o Redundant Intelligence Modules
  - o Resettable circuit breakers
  - o Safety-agency approved
  - o Scalable power capacity
  - o Scalable runtime
  - o SmartSlot
  - o User-replaceable batteries
  - o User-replaceable intelligence modules
  - o User-replaceable power modules
- [more details....](#)

**Topology:** Double Conversion Online

---

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)