





F-81 IN-LINE COUPLER



F-81 WITH NUT & WASHER



F-81 1GHz PERFORMANCE



CATV F-81, BRASS MACHINED - 1 GHz PERFORMANCE WITH 1/2W 1% AUTO-LOAD RESISTOR 25-30db RETURN LOSS



F NUT & WASHER

QUEST offers a series of splices that mate with F series connectors for various mounting applications. These include female-to-female couplers for cable mounting and also versions with nut and washer for panel mounting requirements. QUEST also offers a coupler version designed for 1GHz applications, featuring an auto-termination resistor load design for system balancing when disconnected. Also offered is an F terminator for "dummy load" use.

F SPLICES & COUPLERS

ITEM #	DESCRIPTION
CFS-0181	F-81 IN-LINE COUPLER - FEMALE-TO-FEMALE
CFS-0182	F-81 IN-LINE COUPLER - FEMALE-TO-FEMALE WITH NUT & WASHER
CFS-0186	F-81 1GHz IN-LINE COUPLER WITH AUTO -TERMINATION
CFS-0183	F NUT & WASHER SET


TERMINATOR

ITEM #	DESCRIPTION
CFC-5175	F MALE TERMINATOR - 75 OHM

PLEASE SEE OUR SELECTION OF F TO F AND AUDIO/VIDEO CABLE ASSEMBLIES ON PAGES 66 & 67



F TERMINATOR



For design and manufacturing applications, QUEST offers a selection of panel mounted and board level F connectors. The panel-mounted designs are available for top-threaded or rear mounted bulkhead applications, with solderable center pins. The PC board designs are available for vertical or right angle applications.

QUEST also offers attenuator pads designed to decrease signal levels for testing and calibrating MATV systems. These are offered in female to male configurations in a variety of attenuator values.

PANEL & PC MOUNT


ITEM #	DESCRIPTION
CFS-0185	F-61 F FEMALE CHASSIS MOUNT WITH NUT & WASHER
CFS-0187	F-61 F FEMALE TOP HEX CHASSIS MOUNT WITH NUT & WASHER
CFS-0188	F-61 F FEMALE PC VERTICAL MOUNT
CFS-0189	F-61 F FEMALE RIGHT ANGLE PC MOUNT

ATTENUATORS


ITEM #	DESCRIPTION
CFS-0203	3DB F ATTENUATOR - FEMALE TO MALE
CFS-0206	6DB F ATTENUATOR - FEMALE TO MALE
CFS-0210	10DB F ATTENUATOR - FEMALE TO MALE
CFS-0220	20DB F ATTENUATOR - FEMALE TO MALE

Item #	Insertion Loss (± 1.0Db) 5-860MHz	Return Loss (dB) 5-860MHz
CFS-0203	3	20
CFS-0206	6	20
CFS-0210	10	20
CFS-0220	20	20


**OEM AND SPECIAL DESIGNS
ARE WELCOME**




F-61 CHASSIS MOUNT



F-61 TOP HEX THREAD



**F-61 VERTICAL
CHASSIS MOUNT**



**F-61 RIGHT ANGLE
PC MOUNT**



F ATTENUATOR