

C 091 D

Connector Right Angle



Description	Drawing	No. of cont.	Part Number solder termination	Part Number Crimp termination ¹⁾
Male cable connector right angle 4-6 mm cable diameter, solder or crimp termination Dimension A = 55,5mm	<p>PG 7</p>	3 ³⁾	C091 31K003 100 2	C091 11K003 000 2
		4 ³⁾	C091 31K004 100 2	C091 11K004 000 2
		5	C091 31K005 100 2	C091 11K005 000 2
		5S ³⁾	C091 31K105 100 2	C091 11K105 000 2
		6 ³⁾	C091 31K006 100 2	C091 11K006 000 2
		7	C091 31K007 100 2	C091 11K007 000 2
		7 ³⁾	C091 31K107 100 2	C091 11K107 000 2
		8 ³⁾	C091 31K008 100 2	C091 11K008 000 2
		12	C091 31K012 100 2	–
		14	C091 31K014 100 2	–
Male cable connector right angle 6-8 mm cable diameter, solder or crimp termination Dimension A = 57,5mm	<p>PG 9</p>	5	C091 31K005 101 2	–
		6 ³⁾	C091 11K006 001 2	C091 11K006 001 2
		7	C091 11K007 001 2	C091 11K007 001 2
		7 ³⁾	C091 11K107 001 2	C091 11K107 001 2
		8 ³⁾	C091 11K008 001 2	C091 11K008 001 2
		12	C091 31K012 101 2	–
		14	C091 31K014 101 2	–

¹⁾ Please order crimp contacts separately, see page 44 ³⁾ Contact order for DIN EN 60 130-9 ⁴⁾ For assembly Instructions please refer to page 4, connecting instructions

Assembly instructions ⁴⁾

Can be keyed to 8 angle positions

