

Products > RF ICs/Discretes > PIN Diodes > Axial Glass Packaged > 5082-3080

5082-3080

## axial lead glass packaged PIN diodes

### Description

---

Lifecycle status: **Active**

### Features

---

The 5082-3xx series of current controlled PIN diodes are specified for use in control applications such as variable RF attenuators, AGC circuits, RF modulators, electrically tuned filters, analogue phase shifters, and RF limiters.  $C_t=0.4\text{pF}$ .

**1N5719, 1N5767, 5082-3001, 5082-3039,  
5082-3077, 5082-3080/81, 5082-3188, 5082-3379**



**PIN Diodes for RF Switching and Attenuating**

**Data Sheet**

**Description/Applications**

These general purpose switching diodes are intended for low power switching applications such as RF duplexers, antenna switching matrices, digital phase shifters, and time multiplex filters. The 5082-3188 is optimized for VHF/UHF bandswitching.

The RF resistance of a PIN diode is a function of the current flowing in the diode. These current controlled resistors are specified for use in control applications such as variable RF attenuators, automatic gain control circuits, RF modulators, electrically tuned filters, analog phase shifters, and RF limiters.

Outline 15 diodes are available on tape and reel. The tape and reel specification is patterned after RS-296-D.


**Maximum Ratings**

Junction Operating and  
Storage Temperature Range.....-65°C to +150°C  
Power Dissipation 25°C ..... 250 mW  
(Derate linearly to zero at 150°C)  
Peak Inverse Voltage (PIV) ..... same as  $V_{BR}$   
Maximum Soldering Temperature ..... 260°C for 5 sec

**Features**

- Low Harmonic Distortion
- Large Dynamic Range
- Low Series Resistance
- Low Capacitance

**Outline 15**



DIMENSIONS IN MILLIMETERS AND (INCHES).

## Mechanical Specifications

The Avago Outline 15 package has a glass hermetic seal with dumet leads. The lead finish is 95-5 tin-lead (SnPb) for all PIN diodes. The leads on the Outline 15 package should be restricted so that the bend starts at least 1/16 inch (1.6 mm)

from the glass body. Typical package inductance and capacitance are 2.5 nH and 0.13 pF, respectively. Marking is by digital coding with a cathode band.

## General Purpose Diodes

### Electrical Specifications at $T_A = 25^\circ\text{C}$

Part Number 5082-	Maximum Total Capacitance $C_T$ (pF)	Minimum Breakdown Voltage $V_{BR}$ (V)	Maximum Residual Series Resistance $R_S$ ( $\Omega$ )	Effective Carrier Lifetime $\tau$ (ns)	Reverse Recovery Time $t_r$ (ns)
General Purpose Switching and Attenuating					
3001	0.25	200	1.0	100 (min.)	100 (typ.)
3039	0.25	150	1.25	100 (min.)	100 (typ.)
1N5719	0.3**	150	1.25	100 (min.)	100 (typ.)
3077	0.3	200	1.5	100 (min.)	100 (typ.)
Band Switching					
3188	1.0*	35	0.6**	70 (typ.)*	12 (typ.)
Test Conditions	$V_R = 50\text{ V}$ * $V_R = 20\text{ V}$ ** $V_R = 100\text{ V}$ $f = 1\text{ MHz}$	$V_R = V_{BR}$ Measure $I_R \leq 10\ \mu\text{A}$	$I_F = 100\text{ mA}$ * $I_F = 20\text{ mA}$ ** $I_F = 10\text{ mA}$ $f = 100\text{ MHz}$	$I_F = 50\text{ mA}$ $I_R = 250\text{ mA}$ * $I_F = 10\text{ mA}$ * $I_R = 6\text{ mA}$	$I_F = 20\text{ mA}$ $V_R = 10\text{ V}$ 90% Recovery

#### Notes:

Typical CW power switching capability for a shunt switch in a 50 $\Omega$  system is 2.5 W.

## RF Current Controlled Resistor Diodes

### Electrical Specifications at $T_A = 25^\circ\text{C}$

Part Number	Effective Carrier Lifetime $\tau$ (ns)	Min. Breakdown Voltage $V_{BR}$ (V)	Max. Residual Series Resistance $R_S$ ( $\Omega$ )	Max. Total Capacitance $C_T$ (pF)	High Resistance Limit, $R_H$ ( $\Omega$ )		Low Resistance Limit, $R_L$ ( $\Omega$ )		Max. Difference in Resistance vs. Bias Slope, Dc
					Min.	Max.	Min.	Max.	
5082-3080	1300 (typ.)	100	2.5	0.4	1000			8**	
1N5767*	1300 (typ.)	100	2.5	0.4	1000			8**	
5082-3379	1300 (typ.)	50		0.4				8**	
5082-3081	2500 (typ.)	100	3.5	0.4	1500			8**	
Test Conditions	$I_F = 50\text{ mA}$ $I_R = 250\text{ mA}$	$V_R = V_{BR}$ Measure $I_R \leq 10\ \mu\text{A}$	$I_F = 100\text{ mA}$ $f = 100\text{ MHz}$	$V_R = 50\text{ V}$ $f = 1\text{ MHz}$	$I_F = 0.01\text{ mA}$ $f = 100\text{ MHz}$	$I_F = 1.0\text{ mA}$ $I_F = 20\text{ mA}$ ** $f = 100\text{ MHz}$	Batch Matched at $I_F = 0.01\text{ mA}$ and $1.0\text{ mA}$ $f = 100\text{ MHz}$		

\*The 1N5767 has the additional specifications:  $\tau = 1.0\text{ msec}$  minimum

$I_R = 1\ \mu\text{A}$  maximum at  $V_R = 50\text{ V}$   
 $V_F = 1\text{ V}$  maximum at  $I_F = 100\text{ mA}$ .

### Diode Package Marking

1N5xxx                      5082-xxxx

would be marked:

1Nx                              xx

xxx                              xx

YWW                            YWW

where xxxx are the last four digits of the 1Nxxxx or the 5082-xxxx part number. Y is the last digit of the calendar year. WW is the work week of manufacture.

Examples of diodes manufactured during workweek 45 of 1999:

1N5712                      5082-3080

would be marked:

1N5                              30

712                              80

945                              945

### Part Number Ordering Information

Part Number	No. of devices	Container
5082-3xxx#T25/1N57xx#T25	2500	Tape & Reel
5082-3xxx#T50/ 1N57xx#T50	5000	Tape & Reel
5082-3xxx/ 1N57xx	100	Antistatic bag