


5-Wire *minifast*® Cordsets, Standard

- Straight Male Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 300 V, 9 A



| Housing Style | Part Number | Cable | Features | Pinout |
|---------------|-----------------|--|---|--|
| | RSM 50-*M | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M [†] | <i>flexlife</i> ® | 1. BK 2. BU 3. GN/YE 4. BN 5. WH |
| | RSM 50-*M/S90 | AWM PUR Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50751-*M [†] | <i>Cut/Abrasion Immune</i> | |
| | RSM 50-*M/S1551 | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50578-*M [†] | <i>Yellow conductor instead of Green/Yellow</i> | 1. BK 2. BU 3. YE 4. BN 5. WH |
| | RSM 511-*M | AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50521-*M [†] | <i>flexlife</i> | 1. RD/WH 2. RD/BU 3. GN |
| | RSM 511-*M/S600 | SJOOW CPE Yellow 5x18 AWG 105°C 9.2 mm OD Cable #RF50659-*M [†] | <i>Weld Flash Immune, Flame Immune</i> | 4. RD/OG 5. RD/BK |



* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass "RSM .."; "RS .." indicates nylon and "RSV .." indicates 316 stainless steel.
[†] See Section N for *reelfast*® cable information.