

4-Wire *pico*fast® Cordsets, Threaded Coupling Nut

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 125 VAC/VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	PKW 4M-*	AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M [†]	<i>flexlife</i> ®	
	PKW 4M-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M [†]	<i>Cut/Abrasion Immune</i>	
	PKW 4M-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50935-*M [†]	<i>Cut/Abrasion Immune, flexlife-10, High Flex - Over 10 Million Cycles</i>	
	PKW 4M-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M [†]	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	
	PKW 4M-*/S760	AWM PVC Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50870-*M [†]	<i>flexlife</i>	
	PKW 4M-*/S90/S653	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M [†]	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.
 ** Standard coupling material is nickel plated brass.
 † See Section N for *reelfast*® cable information.