

Description:

24 AWG stranded (7x32) TC conductor, Datalene® insulation, pairs individually shielded with bonded Beldfoil® with a drain wire and have numbered and color-coded PVC jackets, overall Beldfoil® shield/drain wire + overall PVC jacket w/nylon rip cord.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
8	24	7x32	TC - Tinned Copper	.024

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Datalene®	FHDPE - Foam High Density Polyethylene	.068

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Bonded Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: Stranded

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.167

Inner Jacket Color Code Chart:

Number	Color
1	Brown and Numbered 1
2	Red and Numbered 2
3	Orange and Numbered 3
4	Yellow and Numbered 4
5	Green and Numbered 5
6	Blue and Numbered 6
7	Purple and Numbered 7
8	Gray and Numbered 8

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
16	Stranded	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

Overall Cabling

Overall Nominal Diameter: 0.661 in.

Pair

Pair Color Code Chart:

Number	Color
1	Red & Black
2	Red & Black
3	Red & Black
4	Red & Black
5	Red & Black
6	Red & Black
7	Red & Black
8	Red & Black

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +60°C
UL Temperature Rating:	60°C
Bulk Cable Weight:	169 lbs/1000 ft.
Max. Recommended Pulling Tension:	137 lbs.
Min. Bend Radius (Install)/Minor Axis:	6.750 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	AES/EBU

Flame Test

UL Flame Test:	UL1685 FT4 Loading
C(UL) Flame Test:	FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
110

Nom. Inductance:

Inductance (μH/ft)
.18

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
12

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
26

Nominal Velocity of Propagation:

VP (%)
76

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
23.7

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
.384	.46
.7056	.67
.768	.70
1.024	.84
1.4112	1.03
1.536	1.09
2.048	1.30
2.8224	1.66
3.0720	1.76
4.096	2.23
5.6448	2.90
6.144	3.07
8.192	3.71
11.2896	4.53
12.288	4.78
24.576	7.11

Max. Operating Voltage - UL:

Voltage
300 V RMS

Notes (Overall)

Notes: Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1805F Z4B1000	1,000 FT	211.000 LB	VIO Z4B	C	8 #24 PRS FHDPE FS PVC FS PVC
1805F Z4B500	500 FT	106.500 LB	VIO Z4B	C	8 #24 PRS FHDPE FS PVC FS PVC

Notes:

C = CRATE REEL PUT-UP.

AES/EBU Digital Audio Cable

Multi-Pair Snake Cables

Individually Shielded and Jacketed Pairs



Individually Shielded and Jacketed Pairs

NEC: CMG (CEC: CMG FT4)

Product Description

26 AWG or 24 AWG stranded tinned copper conductor. Datalene® insulation. Pairs individually shielded with bonded Beldfoil® with a drain wire and have numbered and color-coded PVC jackets (see Chart 7 in Technical Information Section for colors). Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Overall Beldfoil shield/drain wire plus overall Purple PVC jacket and nylon rip cord.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Color Code: Black, Red.

Specifications

Nominal OD — Conductor

26 AWG	.019" (.48mm)
24 AWG	.024" (.60mm)

Nominal OD — Insulation

26 AWG	.054" (1.37mm)
24 AWG	.070" (1.78mm)

Inner Pair Jacket OD

26 AWG	.136" (3.45mm)
24 AWG	.167" (4.24mm)

Approvals

NEC	CMG
CEC	CMG FT4

Nominal DCR (26 AWG)

Conductor	37.3Ω/M' (122.3Ω/km)
Shield	25.5Ω/M' (83.6Ω/km)

Nominal DCR (24 AWG)

Conductor	23.7Ω/M' (77.7Ω/km)
Shield	18.9Ω/M' (62.0Ω/km)

Nominal Impedance

110Ω ±10Ω

Nominal Velocity of Propagation

76%

Nominal Capacitance (26 AWG)


Between Conductors	12.5 pF/Ft. (41 pF/m)
Between Conductor/Shield*	25 pF/Ft. (82 pF/m)

Nominal Capacitance (24 AWG)

Between Conductors	12 pF/Ft. (39 pF/m)
Between Conductor/Shield*	26 pF/Ft. (86 pF/m)

DCR = DC Resistance

*Capacitance between one conductor and other conductors connected to shield.



Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Individually Shielded & Jacketed NEC: CMG (CEC: CMG FT4)

26 AWG (7x34)

7891A	2	500	152.4	28.0	12.7	.343	8.71
		1000	304.8	56.0	25.5		
7890A	4	100	30.5	8.2	3.7	.399	10.13
		250	76.2	18.0	8.2		
		500	152.4	31.0	14.1		
		1000	304.8	61.0	27.7		
7880A[†]	8	250	76.2	28.0	12.7	.541	13.74
		500	152.4	57.0	25.9		
		1000	304.8	142.0	64.4		

Fits metal shell 25-pin D-sub connectors.

7892A	12	500	152.4	85.5	37.9	.679	17.25
		1000	304.8	174.0	79.1		
7893A	16	500	152.4	109.5	49.8	.770	19.56
		1000	304.8	240.0	109.1		

Individually Shielded & Jacketed NEC: CMG (CEC: CMG FT4)

24 AWG (7x32) • Flexible

1803F	4	500	152.4	57.5	26.1	.488	12.39
		1000	304.8	107.0	48.6		
1805F	8	500	152.4	106.5	48.3	.661	16.79
		1000	304.8	211.0	95.7		
1806F	12	500	152.4	160.0	72.6	.829	21.06
		1000	304.8	330.0	149.7		
1850F	16	500	152.4	208.0	94.4	.944	23.98
		1000	304.8	407.0	184.6		
1852F	24	500	152.4	321.0	145.6	1.205	30.61
		1000	304.8	644.0	292.1		
1854F	32	1000	304.8	841.0	381.5	1.346	34.19

[†]7880A is designed to fit in 25-pin D-sub connectors used in digital console board equipment.