


NEOPRENE JACKET POWER CORDS – Retracted Lengths 1.2 & 4 Feet — Extended Lengths 5, 10 & 20 Feet

UNSHIELDED



DESCRIPTION:

Long-lasting service is assured with this quality multiconductor power cord. Each conductor is stranded copper, with rubber insulation, and a rugged weather and oil resistant neoprene jacket overall.

APPLICATION:

Used on electric tools, portable drills, soldering irons, electrical appliances, household appliances, etc., to eliminate loose hanging wires and to prevent wires from tangling and twisting.

CHARACTERISTICS:

Suggested operating temperature: -20°C to +90°C

OLYMPIC NO.		NO. OF COND.	CONDUCTOR SIZE	CONDUCTOR STRAND	UL/CSA TYPE	AMP RATING	VOLT RATING	NOM. COIL O.D.	NOM. O.D. CORD
1 FT. LENGTHS	2 FT. LENGTHS								
6310E		2	18	41/34	SVEO	7	300	7/8"	.242"
6311E		3	18	41/34	SJEOW/ SJTOW	7	300	1-3/8"	.308"
6312E		3	16	65/34	SJEOW/ SJTOW	10	300	1-3/8"	.365"
6313E	6314E	2	18	41/34	SVEO	7	300	7/8"	.242"
6315	6316	3	18	41/34	SVO	7	300	1"	.275"
6350	6351	2	18	41/34	SJOW	7	300	1-3/16"	.320"
6317E	6318E	3	18	41/34	SJEOW/ SJTOW	7	300	1-3/8"	.308"
6319E	6320E	4*	18	41/34	SJEOW/ SJTOW	5.6	300	1-3/8"	.340"
6352	6353	2	16	65/34	SJOW	10	300	1-3/8"	.360"
6321E	6322E	3	16	65/34	SJEOW/ SJTOW	10	300	1-3/8"	.365"
6354E	6355E	4*	16	65/34	SJEOW/ SJTOW	8	300	1-3/8"	.365"
6356	6357	3	16	65/34	SOW	10	600	1-13/16"	.470"
6358E	6359E	4*	16	65/34	SJEOW/ SJTOW	8	600	1-3/8"	.365"
6360E	6361E	3	14	41/30	SEO	15	600	2-1/8"	.540"
6362E	6363E	4*	14	41/30	SEOW/ STOW	12	600	2-3/8"	.570"

*If all four conductors normally carry current, amp rating is as shown. If one lead is used as a ground, amp rating is the same as 2 and 3 conductor cords.

A 12" retracted length with a 12" straight lead on each end for easy stripping and termination. Cord extends to approximately 6 feet.

COLOR CODE:

- 1 - Black
- 2 - White
- 3 - Green
- 4 - Red