

## Description:

SJT PVC jacket, 300V, 60°C, paper tape separator, smooth jacket, UL/CSA listed, international color code: light blue, brown, green/yellow.

## Physical Characteristics (Overall)

### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
3	14	41x30	BC - Bare Copper

Type of Cordage: SJT

### Insulation

**Insulation Material:**

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.033

### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.038

## Overall Cabling

Overall Cabling Fillers: Jute

**Overall Cabling Color Code Chart:**

Color
Light Blue
Brown
Green/Yellow

Overall Cabling Separator Material: Paper Tape

Overall Nominal Diameter: 0.380 in.

## Mechanical Characteristics (Overall)

UL Temperature Rating: 60°C

Bulk Cable Weight: 92 lbs/1000 ft.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: SJT

CSA Specification: SJT

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

## 19354 Portable Cordage - UL/CSA Types: SJO, SJT

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

CSA Flame Test:	FT2
-----------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Max. Operating Voltage - UL:

<b>Voltage</b>
300 V RMS

### Max. Recommended Current:

<b>Current</b>
18 Amps per conductor @ 25°C
13 Amps per conductor @ 25°C over 50 ft.

<b>Dielectric Withstand Voltage:</b>	1500 V AC Applied For 1 Min.
--------------------------------------	------------------------------

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
19354 010250	250 FT	25.000 LB	BLACK	C	3#14 PVC PVC SJT

### Notes:

C = CRATE REEL PUT-UP.

### 3-Conductor

UL/CSA Types: SJO, SJT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm

**SJO Oil-Resistant Rubber Jacket • Smooth Jacket • UL/CSA Listed**

**300V, 90°C • Paper Tape Separator • Color Code: Black, White, Green**



<b>19229</b>	250 <sup>†</sup>	76.2	14.3	6.5	Black	18 (16x30) BC	.031	.79	.039	.99	.315	8.00
<b>19230</b>	250 <sup>†</sup>	76.2	17.8	8.1	Black	16 (26x30) BC	.031	.79	.038	.97	.340	8.64

**SJT PVC Jacket • Serrated Jacket • UL/CSA Listed**

**300V, 60°C • Paper Tape Separator • Color Code: Black, White, Green (18 AWG); Black, White, Green/Yellow (16 AWG)**



<b>19348</b>	250 <sup>†</sup>	76.2	17.3	7.8	Gray, Black	18 (42x34) BC	.032	.81	.046	1.17	.328	8.33
<b>19349</b>	250 <sup>†</sup>	76.2	18.3	8.3	Gray, Black	16 (65x34) BC	.033	.83	.038	.97	.340	8.64

**SJT PVC Jacket • Smooth Jacket • UL/CSA Listed**

**300V, 60°C • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow**



<b>19352</b>	250	76.2	17.5	8.0	Black	18 (42x34) BC	.032	.81	.046	1.17	.328	8.33
<b>19353</b>	250	76.2	20.0	9.1	Black	16 (65x34) BC	.033	.84	.036	.91	.353	8.97
<b>19354</b>	250	76.2	25.0	11.4	Black	14 (41x30) BC	.033	.84	.038	.97	.380	9.65

**SJT PVC Jacket • Shielded • Smooth Jacket • 20 AWG Drain Wire (7x28) • UL/CSA Listed**


**300V, 60°C Shielded • Beldfoil® Shield (100% Coverage) • International Color Code: Light Blue, Brown, Green/Yellow**



<b>19362</b>	250	76.2	17.3	7.8	Black	18 (42x34) BC	.032	.81	.050	1.27	.340	8.64
	500	152.4	35.0	15.9								
<b>19363</b>	250	76.2	21.3	9.7	Black	16 (65x34) BC	.033	.84	.047	1.19	.365	9.27
<b>19364</b>	250	76.2	26.3	11.9	Black	14 (41x30) BC	.033	.84	.042	1.07	.402	10.21

**SJT PVC Jacket • Low Leakage Power Cord • Smooth Jacket • UL Listed**

**300V, 75°C • Paper Tape Separator • Color Code: Black, White, Green**



<b>9998*</b>	500 <sup>††</sup>	152.4	55.5	25.2	Gray	16 (65x34) Bare Copper	.033	.84	.045	1.14	.475	12.07
	1000 <sup>††</sup>	304.8	107.0	48.5	Lt. Blue							

BC = Bare Copper

\*Not CSA recognized.

<sup>†</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

<sup>††</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 100 ft.