

1B25A Tools and Accessories - 75-Ohm BNC Connector

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : ConnectorTermination.pdf</p>
--	--

Description:

One-piece, male connector for Mini Hi-Res coaxial cable.

SUITABLE APPLICATIONS:

Suitable Applications	Mini Hi-Res Coaxial Cable
-----------------------	---------------------------

PHYSICAL CHARACTERISTICS:

Connector Interface	BNC
Connector Cable Type	Mini RGB
AWG of Cable	25
Ohms	75 Ohms
Contact Plating	AU
Contact Attachment Method	Compression
Body Plating	NI
Body Attachment Method	Compression
Tool Requirements	Belden HCCT
Die Required	BNC/RCA

APPLICABLE STANDARDS:

EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy)	04/01/2005

NOTES:

Notes	Insertion Loss: <0.1 dB @ 1 GHz
Notes (Cont'd.)	Return Loss: >20 dB, 5 - 1000 MHz

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1B25A 000B100	BNC CONN MINI-RGB W/O FERRELL	B100	3.5	NONE	Q

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 1 Revision Date: 01-03-2006

1B25A Tools and Accessories - 75-Ohm BNC Connector

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.