

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power



Description:

Coax:20 AWG solid BC cond., gas-injected foam HDPE insul., 95% BC braid shield, PVC jacket, cabled with(1) pair - 23 AWG solid BC conductor, PO insulation, PVC Jacket, and cabled with (2) conductors, 18 AWG (7x26) BC conductors, PP insulation,PVC jacket

Coax

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	0.032

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected PHDPE - Foam High Density Polyethylene	0.145

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.227

Outer Jacket Color Code Chart:

Number	Color
Video	Black

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU CE Mark:	Yes
RG Type:	59/U

Flame Test

UL Flame Test:	UL1666 Vertical Shaft
----------------	-----------------------

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

75

Nom. Inductance:

Inductance (µH/ft)
0.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
16.300

Nominal Velocity of Propagation:

VP (%)
83.000

Nominal Delay:

Delay (ns/ft)
1.220

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
10.000

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
3.500

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.300
5.000	0.650
10.000	0.900
50.000	1.900
100.000	2.600
200.000	3.600
400.000	5.000
700.000	7.000
900.000	8.000
1000.000	8.500

Max. Operating Voltage - UL: 300 V RMS

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	23	Solid	BC - Bare Copper	0.023

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PO - Polyolefin	0.041

Twisted Pair Color Code Chart:

Number	Color
1	Blue and White/Blue

Outer Shield

Outer Shield Material:

Type	Dia. (in.)
PVC - Polyvinyl Chloride	0.118

Outer Jacket

Outer Jacket Color Code Chart:

Number	Color
--------	-------

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

1	Blue
---	------

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
15.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
20.000

Max. Operating Voltage - Other:

Voltage
300 V RMS

Max. Recommended Current:

Current
2.4 Amps per conductor @ 25°C

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	18	7x26	BC - Bare Copper	0.047

Insulation

Insulation Material:

Insulation Material
PP - Polypropylene

Insulation Color Code Chart:

Number	Color
1	Red
2	Black

Individual Shield

Individual Shield Color Code Chart:

.

Outer Jacket

Outer Jacket Diameter:

Nom. Dia. (in.)
0.158

Outer Jacket Color Code Chart:

Number	Color
1	White

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

Flame Test

UL Flame Test:	UL1666 Vertical Shaft
----------------	-----------------------

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Electrical Characteristics**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)

21.500

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.500

Max. Operating Voltage - Other:

Voltage

300 V RMS

Physical Characteristics (Overall)**Conductor****Outer Jacket****Outer Jacket Material:**

Outer Jacket Material

Unjacketed

Overall Cabling

Overall Nominal Diameter:	0.411 in.
---------------------------	-----------

Mechanical Characteristics (Overall)

Operating Temperature Range:	-10°C To +75°C
------------------------------	----------------

Separation Temperature Range:	0°C To +75°C
-------------------------------	--------------

Bulk Cable Weight:	60.000 lbs/1000 ft.
--------------------	---------------------

Max. Recommended Pulling Tension:	115.000 lbs.
-----------------------------------	--------------

Min. Bend Radius (Install)/Minor Axis:	4.100 in.
--	-----------

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2002/95/EC (RoHS):	Yes
---------------------------------	-----

EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
---------------------------------------	------------

EU Directive 2002/96/EC (WEEE):	Yes
---------------------------------	-----

EU Directive 2003/11/EC (BFR):	Yes
--------------------------------	-----

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Plenum Number:	600PTZ
----------------	--------

Notes (Overall)

Notes: RG59 CCTV + 1PR23 UTP + 2C 18 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation. Banana Peel® US Patent 7049523.

500PTZ Composite - For PTZ Cameras: CCTV + Control + Power

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
500PTZ 0001000	1,000 FT	58.000 LB	NONE	C	1 RG59 + 1 UTP 23 + 2C18
500PTZ 000500	500 FT	29.500 LB	NONE	C	1 RG59 + 1 UTP 23 + 2C18

Notes:

C = CRATE REEL PUT-UP.

Sound, Security and Alarm Cables

Cable Finder Guide — Coax and Composite



Coax Series or Component Type	AWG Size	Stranding	Non-Plenum				Plenum			
			Part No.	Rating	Shield/Braid Coverage	Page No.	Part No.	Rating	Shield/Braid Coverage	Page No.
CATV/MATV Coax										
RG-59/U	20	Solid	—	—	—	—	6439C8	CMP	Duofoil + 80% Aluminum	20.49
	20	Solid	—	—	—	—	6439Q8	CMP	Quad Shield	20.49
RG-6/U	18	Solid	5339B5	CM	Duofoil + 60% Aluminum	20.48	633938	CMP	Duofoil + 90% Aluminum	20.49
	18	Solid	5339Q5	CM	Quad Shield	20.48	6339Q8	CMP	Quad Shield	20.49
RG-11/U	14	Solid	—	—	—	—	6139B8	CMP	Duofoil + 60% Aluminum	20.49
CCTV Coax										
Mini 59	25	Solid	573945	CM	94% Bare Copper	20.37	673948	CMP	95% Bare Copper	20.39
RG-59/U	22	7	551945	CM	95% Bare Copper	20.37	—	—	—	—
	20	Solid	543945	CM	95% Bare Copper	20.37	643948	CMP	95% Bare Copper	20.39
RG-6/U	18	Solid	533945	CM	95% Bare Copper	20.37	633948	CMP	95% Bare Copper	20.39
RG-11/U	14	Solid	513945	CM	95% Bare Copper	20.37	613948	CMP	95% Bare Copper	20.39
CCTV Coax, Surveillance										
RG-59/U	20	Solid	—	—	—	—	7986LC	CMP	95% Bare Copper	20.50
RG-6/U	18	Solid	—	—	—	—	7985LC	CMP	95% Bare Copper	20.50
CATV Coax, Water-blocked										
RG-59/U	20	Solid	5439W5	CM	Duofoil® + 95% TC	20.37	—	—	—	—
RG-6/U	18	Solid	5339W5	CM	Duofoil + 60% Aluminum	20.37	—	—	—	—
Security Coax										
RG-62	22	Solid	—	—	—	—	6539Y8	CMP	95% Bare Copper	20.39
Schlage Coax										
RG-6/U	18	Solid	5399B5	CM	Duobond® + 60% Alum.	20.48	—	—	—	—
CCTV Composite Coax with Unshielded Pair for Control or Power										
Mini RG-59	25	Solid	579945	CM	95% Bare Copper	20.38	679948	CMP	95% Bare Copper	20.38
UTP	20	7	—	—	Unshielded	—	—	—	Unshielded	—
RG-59	20	Solid	549945	CM	95% Bare Copper	20.38	649948	CMP	95% Bare Copper	20.38
UTP	18	7	—	—	Unshielded	—	—	—	Unshielded	—
RG-6	18	Solid	539945	CM	95% Bare Copper	20.38	639948	CMP	95% Bare Copper	20.38
UTP	18	7	—	—	Unshielded	—	—	—	Unshielded	—
Pan/Tilt/Zoom BananaPeel Composite Coax										
RG-59/U	20	Solid	500PTZ	CMR	95% Bare Copper Braid	20.42	600PTZ	CMP	95% Bare Copper Braid	20.43
1UTP	23	Solid	—	—	Unshielded	—	—	—	Unshielded	—
2/C	18	7	—	—	Unshielded	—	—	—	Unshielded	—
RG-59/U	20	Solid	501PTZ	CMR	95% Bare Copper Braid	20.44	601PTZ	CMP	95% Bare Copper Braid	20.45
1STP	22	7	—	—	Beldfoil®	—	—	—	Beldfoil	—
2/C	18	7	—	—	Unshielded	—	—	—	Unshielded	—
RG-59/U	20	Solid	502PTZ	CMR	95% Bare Copper Braid	20.46	602PTZ	CMP	95% Bare Copper Braid	20.47
1STP	18	7	—	—	Beldfoil	—	—	—	Beldfoil	—
2/C	18	7	—	—	Unshielded	—	—	—	Unshielded	—
CCTV Surveillance UTP and Composite Cables										
2/C	16	19	5284US	CMR	Unshielded	20.51	6284US	CMP	Unshielded	20.52
2TP	24	Solid	—	—	Unshielded	—	—	—	Unshielded	—
2/C	16	19	5284UE	CMR	Unshielded	20.51	6284UE	CMP	Unshielded	20.52
2TP	23	Solid	—	—	Unshielded	—	—	—	Unshielded	—
2/C	16	19	5288US	CMR	Unshielded	20.51	6288US	CMP	Unshielded	20.52
4TP	23	Solid	—	—	Unshielded	—	—	—	Unshielded	—
4TP	24	Solid	1583A	CM	Unshielded	20.40/53	1585A	CMP	Unshielded	20.41/54
4TP	24	Solid	1500A	CM	Unshielded	20.40/53	1501A	CMP	Unshielded	20.41/54
4TP	24	Solid	1583R	CMR	Unshielded	20.40/53	—	—	—	—
2TP	24	Solid	1500R	CMR	Unshielded	20.40/53	—	—	—	—
4TP	23	Solid	7881A	CMR	Unshielded	20.40/53	7882A	CMP	Unshielded	20.41/54
Access Control BananaPeel® Composite Cables										
4/C	18	7	558AFS	CMR	Beldfoil	20.36	658AFS	CMP	Beldfoil	20.35
3TP	22	7	—	—	Beldfoil	—	—	—	Beldfoil	—
4/C	22	7	—	—	Beldfoil	—	—	—	Beldfoil	—
2/C	22	7	—	—	Beldfoil	—	—	—	Beldfoil	—
4/C	16	19	538AFS	CMR	Beldfoil	20.36	638AFS	CMP	Beldfoil	20.35
3TP	18	7	—	—	Beldfoil	—	—	—	Beldfoil	—
4/C	18	7	—	—	Beldfoil	—	—	—	Beldfoil	—
2/C	18	7	—	—	Beldfoil	—	—	—	Beldfoil	—

STP = Shielded Twisted Pair • TC = Tinned Copper • TP = Twisted Pair(s) • UTP = Unshielded Twisted Pair • /C = Conductor(s) (Multi-conductor)

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Riser-Rated



Composite Coax, Pair and Multi-Conductors

CMR/CMG FT4 Rated

Product Description

(1) Coax: 20 AWG solid bare copper conductor, gas-injected foam high-density polyethylene insulation, bare copper braid shield (95% coverage), Black PVC jacket.

(1) Pair: 23 AWG solid bare copper conductors, polyolefin insulation, Blue PVC jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, PVC insulation, White flame-retardant PVC jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Unshielded
Power	Unshielded
Component Jackets	PVC
Overall Jacket	None
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite (NEC CMR and CEC CMG FT4)

RG-59/U 20 AWG Coax • Cat. 5e 23 AWG Pair • 18 AWG Cond.										
500PTZ <small>NEW</small>	(1) Coax:	Gas-injected	.227	5.57	.411	10.4	500	152	38.5	17.5
	RG-59/U	Foam HDPE,					1000	305	71.0	32.3
	20 AWG	Bare Copper								
	(solid)	Braid Shield								
	Bare Copper	(95% coverage)								
	Cond.									
	(1) 1-Pair	Polyolefin,	.118	3.00						
	23 AWG	Unshielded								
	(solid)									
	Bare Copper									
	Cond.									
	(1) 2-Cond.	PVC,	.171	4.34						
	18 AWG	Unshielded								
	Stranded									
	(7x26)									
	Bare Copper									
	Cond.									

HDPE = High-density Polyethylene
U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax, RG-59/U, 20 AWG, 95% Braid
Blue	1/P, 23 AWG, Unshielded
White	2/C, 18 AWG, Unshielded