



Description:

20 AWG solid bare copper conductor, foam polyethylene insulation, bare copper braid shield, PVC jacket, sequential footage marking every two feet.

Usage (Overall)

Suitable Applications: Analog Video/CCTV Coax.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	.032

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FPE - Foam Polyethylene	.145

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	90.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.232 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 29 lbs/1000 ft.

Max. Recommended Pulling Tension: 57 lbs.

Min. Bend Radius (Install)/Minor Axis: 2.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMG

NEC Articles: 800

CEC/C(UL) Specification: CMG

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

543945 Coax - Surveillance and CCTV Applications

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 59/U

Series Type: Series 59

Flame Test

UL Flame Test: UL1685 FT4/IEEE 1202 Vertical Tray Flame Test

C(UL) Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: Yes - Black only.

Suitability - Aerial: Yes - Black only.

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/ft)

.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.3

Nominal Velocity of Propagation:

VP (%)

83

Nominal Delay:

Delay (ns/ft)

1.21

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

10.0

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.300

Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100 ft.)

1	.30
5	.65
10	.90
50	1.90
100	2.60
200	3.60
400	5.00
700	7.00
900	8.00

543945 Coax - Surveillance and CCTV Applications

1000	8.50
------	------

Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
5.000	0.750
50.000	2.150

Max. Operating Voltage - UL:

Voltage
300 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
543945 009U1000	1,000 FT	31.000 LB	WHITE		RG-59/U COAX
543945 009U500	500 FT	16.000 LB	WHITE		RG-59/U COAX
543945 0091000	1,000 FT	32.000 LB	WHITE	C	RG-59/U COAX
543945 009500	500 FT	16.000 LB	WHITE		RG-59/U COAX
543945 010U1000	1,000 FT	31.000 LB	BLACK		RG-59/U COAX
543945 010U500	500 FT	16.000 LB	BLACK		RG-59/U COAX
543945 0101000	1,000 FT	32.000 LB	BLACK	C	RG-59/U COAX
543945 010500	500 FT	16.000 LB	BLACK	C	RG-59/U COAX

Notes:

C = CRATE REEL PUT-UP.