

Description:

22 AWG stranded (7x30) TC conductor, FEP insulation, twisted pairs individually shielded with Beldfoil® (100% coverage), overall jacket per table below, 22 AWG stranded TC drain wire.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
6	22	7x30	TC - Tinned Copper	.030

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FEP - Fluorinated Ethylene Propylene	.050

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
22

Inner Shield Drain Wire Stranding: Stranded

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Overall Cabling

Overall Nominal Diameter: 0.314 in.

Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown

Pair Lay Length & Direction:

Lay Length (in.)	Twists/ft. (twist/ft)	Direction

82778 Multi-Conductor - CMP Rated (Plenum) Cable

1.000	12.000	Left Hand Lay
-------	--------	---------------

Mechanical Characteristics (Overall)

Operating Temperature Range:	0°C To +60°C
Bulk Cable Weight:	63 lbs/1000 ft.
Min. Bend Radius (Install)/Minor Axis:	3.250 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	8778

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
46

Nom. Inductance:

Inductance (µH/ft)
0.18

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
35

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
76

Nominal Velocity of Propagation:

VP (%)
62

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
16

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C:	11.300 Ohm/1000 ft
---	--------------------

Max. Operating Voltage - UL:

Voltage

82778 Multi-Conductor - CMP Rated (Plenum) Cable

300 V RMS

Max. Recommended Current:

Current

1.96 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
82778 8771000	1,000 FT	71.000 LB	NATURAL	C	6PR#22 FS FEP FLMRST

Notes:

C = CRATE REEL PUT-UP.


Individually Shielded

Audio, Control and Instrumentation Cables
Plenum-Rated and Non-Plenum


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire


Plenum • FEP Insulation • Natural Flamarrest® Jacket

 300V RMS Z-Fold®	82777	NEC:	3	See	U-500†	U-152.4	19.5	8.9	14.7Ω/M'	11.3Ω/M'	.237	6.02	46	62%	35	115	76	249	
		CMP		Chart 3	U-1000	U-304.8	38.0	17.3	48.2Ω/km	37.1Ω/km									
		CEC:		(Tech Info Section)	1000†	304.8	39.0	17.7											
		CMP FT6																	
	82778	NEC:	6	See	1000†	304.8	71.0	32.2	14.7Ω/M'	11.3Ω/M'	.314	7.98	46	62%	35	115	76	249	
CMP			Chart 3					48.2Ω/km	37.1Ω/km										
CEC:			(Tech Info Section)																
CMP FT6																			

Plenum • FEP Insulation • Red FEP Jacket


 300V RMS Z-Fold®	88777	NEC:	3	See	100	30.5	6.0	2.7	14.7Ω/M'	11.3Ω/M'	.234	5.94	50	69%	31	102	67	220	
		CMP		Chart 3	500†	152.4	19.0	8.6	48.2Ω/km	37.1Ω/km									
		CEC:		(Tech Info Section)	1000†	304.8	42.0	19.1											
		CMP FT6																	
	88778	NEC:	6	See	100	30.5	7.0	3.2	14.7Ω/M'	11.3Ω/M'	.309	7.85	50	69%	31	102	67	220	
CMP			Chart 3	500†	152.4	38.5	17.4	48.2Ω/km	37.1Ω/km										
CEC:			(Tech Info Section)	1000†	304.8	75.0	34.1												
CMP FT6																			

Plenum • FEP Insulation • Red Fluorocopolymer Jacket

 300V RMS Z-Fold®	87777	NEC:	3	See	500†	152.4	18.0	8.2	14.7Ω/M'	11.3Ω/M'	.234	5.94	50	69%	31	102	67	220	
		CMP		Chart 3	1000†	304.8	40.0	18.2	48.2Ω/km	37.1Ω/km									
		CEC:		(Tech Info Section)															
		CMP FT6																	
	87778	NEC:	6	See	500†	152.4	37.5	17.0	14.7Ω/M'	11.3Ω/M'	.309	7.85	50	69%	31	102	67	220	
CMP			Chart 3	1000†	304.8	73.0	33.2	48.2Ω/km	37.1Ω/km										
CEC:			(Tech Info Section)																
CMP FT6																			


20 AWG Stranded (7x28) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil (100% Coverage) • 22 AWG Stranded TC Drain Wire

Semi-rigid PVC Insulation • Overall Chrome PVC Jacket

 UL AWM Style 2464 (300V 80°C) Z-Fold®	9402	NEC:	2	Red & Black,	U-500	U-152.4	26.0	11.8	—	—	.300	7.62	—	—	55	180	95	312	
		CMG		Green & White	1000	304.8	52.0	23.7											
		CEC:																	
		CMG FT4																	

20 AWG Stranded (10x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil (100% Coverage) • 22 AWG Stranded TC Drain Wire

Polypropylene Insulation • Black High-density Polyethylene Jacket

 350V Z-Fold®	9883		3	See	500	152.4	28.5	12.9	6.4Ω/M'	11.2Ω/M'	.340	8.64	50	66%	30	98	55	180	
				Chart 3	1000	304.8	57.0	25.9	21.0Ω/km	36.8Ω/km									
				(Tech Info Section)															
	9886		6	See	500	152.4	56.0	25.4	6.4Ω/M'	11.2Ω/M'	.455	11.56	50	66%	30	98	55	180	
			Chart 3	1000	304.8	108.0	49.0	21.0Ω/km	36.8Ω/km										
			(Tech Info Section)																

DCR = DC Resistance • TC = Tinned Copper

* Capacitance between conductors.

** Capacitance between one conductor and other conductors connected to shield.

† Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.