



Description:

22 AWG stranded (7x30) TC conductors, conductors cabled, 22 AWG (7x30) stranded TC drain wire, FEP insulation, special Beldfoil® shield (100% coverage), silicone rubber jacket, noise reducing tape.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
4	22	7x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (in.)
Teflon®	FEP - Fluorinated Ethylene Propylene	.015

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Tape	Noise Reducing Conductive Nylon	

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
Silicone Rubber	.030

Overall Cabling

Overall Cabling Lay Length & Direction:

Length (in.)	Twists (ft.)
1	12

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	White
3	Red
4	Green

Overall Nominal Diameter: 0.217 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +150°C

Bulk Cable Weight: 32 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius (Install)/Minor Axis: 2.250 in.

83396 Multi-Conductor - Control and Instrumentation Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading, VW-1
----------------	-------------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
22

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
40

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
17.5

Max. Operating Voltage - UL:

Voltage	Description
2000 V DC	through jacket
350 V RMS	between conductors

Max. Recommended Current:

Current
2.8 Amps per conductor @ 25°C

Notes (Overall)

Notes (Cont'd.): Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83396 002100	100 FT	3.900 LB	RED		4 #22 FEP FS SIL
83396 002500	500 FT	16.000 LB	RED	C	4 #22 FEP FS SIL

Notes:
C = CRATE REEL PUT-UP.

High-Temperature

Overall Beldfoil® Shield

Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Conductors Cabled • Special Beldfoil Shield (100% Coverage) • 22 AWG (7x30) Stranded TC Drain Wire

FEP Insulation • Red Silicone Rubber Jacket • Noise Reducing Tape

Jacket working voltage 2000V DC, shield to ground VW-1	83394	AWM 4516	2	Black, White	100 500†	30.5 U-152.4	3.6 14.5	1.6 6.6	.015 500†	.38 152.4	.030 13.0	.76 5.9	.199	5.05	22	72	40	131
--------------------------------------------------------------	--------------	-------------	---	-----------------	-------------	-----------------	-------------	------------	--------------	--------------	--------------	------------	------	------	----	----	----	-----



70°C (min.) to 150°C (max.) operating temperature.

Jacket working voltage 2000V DC, shield to ground VW-1	83395	AWM 4516	3	Black, Red, White	100 500†	30.5 152.4	3.9 14.0	1.8 6.4	.015	.38	.031	.79	.208	5.28	22	72	40	131
--------------------------------------------------------------	--------------	-------------	---	-------------------------	-------------	---------------	-------------	------------	------	-----	------	-----	------	------	----	----	----	-----



70°C (min.) to 150°C (max.) operating temperature.

	83396	AWM 4516	4	Black, White, Red, Green	100 500†	30.5 152.4	3.9 16.0	1.8 7.3	.015	.38	.030	.76	.217	5.51	22	72	40	131
--	--------------	-------------	---	-----------------------------------	-------------	---------------	-------------	------------	------	-----	------	-----	------	------	----	----	----	-----

20 AWG Stranded (7x28) TC Conductors • Twisted Pair • Special Beldfoil Shield (100% Coverage) • 20 AWG (7x28) Stranded TC Drain Wire

FEP Insulation • Yellow Silicone Rubber Jacket • Noise Reducing Tape

Jacket working voltage 2000V DC, shield to ground VW-1	83393	AWM 4516	2	Black, Red	100†† 500†	30.5 U-152.4	4.2 18.5	1.9 8.4	.020 500†	.51 152.4	.030 17.0	.76 7.8	.242	6.15	22	72	40	131
--------------------------------------------------------------	--------------	-------------	---	---------------	---------------	-----------------	-------------	------------	--------------	--------------	--------------	------------	------	------	----	----	----	-----



70°C (min.) to 150°C (max.) operating temperature.

20 AWG Stranded (7x28) TC Conductors • Conductors Cabled • Overall Beldfoil Shield (100% Coverage) • Drain Wire

Tefzel® Insulation • Clear Tefzel Jacket

300V RMS 150°C VW-1	85230	—	2	Black, Red	500† 1000†	152.4 304.8	12.5 29.0	5.7 13.2	.015	.38	.020	.51	.182	4.62	31	102	59	194
------------------------	--------------	---	---	---------------	---------------	----------------	--------------	-------------	------	-----	------	-----	------	------	----	-----	----	-----



300V RMS 150°C VW-1	85240	—	3	Black, Red, Green	100 1000†	30.5 304.8	4.6 30.0	2.1 13.6	.015	.38	.020	.51	.193	4.90	27	87	48	157
------------------------	--------------	---	---	-------------------------	--------------	---------------	-------------	-------------	------	-----	------	-----	------	------	----	----	----	-----



16 AWG Stranded (19x29) TC Conductors • Conductors Cabled • Overall Beldfoil Shield (100% Coverage) • Drain Wire

Tefzel Insulation • Clear Tefzel Jacket

300V RMS 150°C VW-1	85231	—	2	Black, Red	100 500† 1000†	30.5 152.4 304.8	5.6 17.0 38.0	2.5 7.8 17.3	.020	.51	.020	.51	.210	5.33	44	144	79	259
------------------------	--------------	---	---	---------------	----------------------	------------------------	---------------------	--------------------	------	-----	------	-----	------	------	----	-----	----	-----



300V RMS 150°C VW-1	85241	—	3	Black, Red, Green	500† 1000†	152.4 304.8	22.5 49.0	10.3 22.3	.020	.51	.020	.51	.223	5.66	34	112	61	201
------------------------	--------------	---	---	-------------------------	---------------	----------------	--------------	--------------	------	-----	------	-----	------	------	----	-----	----	-----



TC = Tinned Copper

*Capacitance between conductors. **Capacitance between one conductor and other conductors connected to shield.
†Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.
††100 ft. put-up one piece, exact length.

Tefzel and Kapton are DuPont trademarks.