

8503 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

Tinned copper conductor, PVC insulation. Covers insulated wire for internal wiring of meters, panels, and electrical or electronic equipment. Temperatures to 105°C.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	22
Stranding	7x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.010 in.

OVERALL:

Overall Nominal Diameter	.050 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2006
Military Specification	MIL-W-16878E/1
MIL Spec Rating	600 V, 105°C

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8503 001100	22 STR PVC BRN	100	0.3	BROWN	
8503 0011000	22 STR PVC BRN	1000	4	BROWN	P

8503 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

8503 001D100	22 STR PVC BRN	D100	0.3	BROWN	
8503 001D1000	22 STR PVC BRN	D1000	4	BROWN	
8503 002100	22 STR PVC RED	100	0.3	RED	
8503 0021000	22 STR PVC RED	1000	4	RED	P
8503 002D100	22 STR PVC RED	D100	0.3	RED	
8503 002D1000	22 STR PVC RED	D1000	4	RED	
8503 002D5000	22 STR PVC RED	D5000	15	RED	
8503 003100	22 STR PVC ORG	100	0.3	ORANGE	
8503 0031000	22 STR PVC ORG	1000	4	ORANGE	P
8503 003D100	22 STR PVC ORG	D100	0.3	ORANGE	
8503 003D1000	22 STR PVC ORG	D1000	4	ORANGE	
8503 003D5000	22 STR PVC ORG	D5000	15	ORANGE	
8503 004100	22 STR PVC YEL	100	0.3	YELLOW	
8503 0041000	22 STR PVC YEL	1000	4	YELLOW	P
8503 004D100	22 STR PVC YEL	D100	0.3	YELLOW	
8503 004D1000	22 STR PVC YEL	D1000	4	YELLOW	
8503 004D5000	22 STR PVC YEL	D5000	15	YELLOW	
8503 005100	22 STR PVC GRN	100	0.3	GREEN, DARK	
8503 0051000	22 STR PVC GRN	1000	4	GREEN, DARK	P
8503 005D100	22 STR PVC DGRN	D100	0.3	GREEN, DARK	
8503 005D1000	22 STR PVC DGRN	D1000	4	GREEN, DARK	
8503 005D5000	22 STR PVC DGRN	D5000	15	GREEN, DARK	
8503 006100	22 STR PVC LBLU	100	0.3	BLUE, LIGHT	
8503 0061000	22 STR PVC LBLU	1000	4	BLUE, LIGHT	P
8503 006D100	22 STR PVC LBLU	D100	0.3	BLUE, LIGHT	
8503 006D1000	22 STR PVC LBLU	D1000	4	BLUE, LIGHT	
8503 006D5000	22 STR PVC LBLU	D5000	15	BLUE, LIGHT	
8503 007100	22 STR PVC VIO	100	0.3	VIOLET	

8503 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

8503 0071000	22 STR PVC VIO	1000	4	VIOLET	P
8503 007D100	22 STR PVC VIO	D100	0.3	VIOLET	
8503 007D1000	22 STR PVC VIO	D1000	4	VIOLET	
8503 008100	22 STR PVC GRY	100	0.3	GRAY	
8503 0081000	22 STR PVC GRY	1000	4	GRAY	P
8503 008D100	22 STR PVC GRY	D100	0.3	GRAY	
8503 008D1000	22 STR PVC GRY	D1000	4	GRAY	
8503 009100	22 STR PVC WHT	100	0.3	WHITE	
8503 0091000	22 STR PVC WHT	1000	4	WHITE	P
8503 009D100	22 STR PVC WHT	D100	0.3	WHITE	
8503 009D1000	22 STR PVC WHT	D1000	4	WHITE	
8503 009D5000	22 STR PVC WHT	D5000	15	WHITE	
8503 010100	22 STR PVC BLK	100	0.3	BLACK	
8503 0101000	22 STR PVC BLK	1000	4	BLACK	P
8503 010D100	22 STR PVC BLK	D100	0.3	BLACK	
8503 010D1000	22 STR PVC BLK	D1000	4	BLACK	
8503 010D5000	22 STR PVC BLK	D5000	15	BLACK	
8503 014100	22 STR PVC WHT/BLK	100	0.3	WHITE/BLACK	A
8503 0141000	22 STR PVC WHT/BLK	1000	4	WHITE/BLACK	A
8503 015100	22 STR PVC WHT/RED	100	0.3	WHITE/RED	A
8503 0151000	22 STR PVC WHT/RED	1000	4	WHITE/RED	A
8503 016100	22 STR PVC WHT/GRN	100	0.3	WHITE/GREEN	A
8503 0161000	22 STR PVC WHT/GRN	1000	4	WHITE/GREEN	A
8503 0171000	22 STR PVC WHT/YEL	1000	4	WHITE/YELLOW	A
8503 018100	22 STR PVC WHT/BLU	100	0.3	WHITE/BLUE	A
8503 0181000	22 STR PVC WHT/BLU	1000	4	WHITE/BLUE	A
8503 019100	22 STR PVC WHT/BRN	100	0.3	WHITE/BROWN	A
8503 0191000	22 STR PVC WHT/BRN	1000	4	WHITE/BROWN	A

8503 Hook-up/Lead - (Type B) MIL-W-16878/1-PVC

8503 020100	22 STR PVC WHT/ORG	100	0.3	WHITE/ORANGE	A
8503 0201000	22 STR PVC WHT/ORG	1000	4	WHITE/ORANGE	A
8503 0211000	22 STR PVC WHT/GRY	1000	4	WHITE/GRAY	A
8503 022100	22 STR PVC WHT/VIO	100	0.3	WHITE/VIOLET	A
8503 0221000	22 STR PVC WHT/VIO	1000	4	WHITE/VIOLET	A

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 03-10-2007

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.