




8520 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	14
Stranding	41x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.018 in.

OVERALL:

Overall Nominal Diameter	.111 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
Military Specification	MIL-W-76C
MIL Spec Rating	1000 V, 80°C

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8520 001100	14 STR PVC BRN	100	1.9	BROWN	

8520 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

8520 0011000	14 STR PVC BRN	1000	17	BROWN	P
8520 002100	14 STR PVC RED	100	1.9	RED	
8520 0021000	14 STR PVC RED	1000	17	RED	P
8520 003100	14 STR PVC ORG	100	1.9	ORANGE	
8520 0031000	14 STR PVC ORG	1000	17	ORANGE	P
8520 004100	14 STR PVC YEL	100	1.9	YELLOW	
8520 0041000	14 STR PVC YEL	1000	17	YELLOW	P
8520 005100	14 STR PVC GRN	100	1.9	GREEN, DARK	
8520 0051000	14 STR PVC GRN	1000	17	GREEN, DARK	P
8520 006100	14 STR PVC LBLU	100	1.9	BLUE, LIGHT	
8520 0061000	14 STR PVC LBLU	1000	17	BLUE, LIGHT	P
8520 007100	14 STR PVC VIO	100	1.9	VIOLET	
8520 0071000	14 STR PVC VIO	1000	17	VIOLET	P
8520 008100	14 STR PVC GRY	100	1.9	GRAY	
8520 0081000	14 STR PVC GRY	1000	17	GRAY	P
8520 009100	14 STR PVC WHT	100	1.9	WHITE	
8520 0091000	14 STR PVC WHT	1000	17	WHITE	P
8520 010100	14 STR PVC BLK	100	1.9	BLACK	
8520 0101000	14 STR PVC BLK	1000	17	BLACK	P
8520 011100	14 STR PVC TAN	100	1.9	TAN	
8520 013100	14 STR PVC DBLU	100	1.9	BLUE, DARK	
8520 0131000	14 STR PVC DBLU	1000	17	BLUE, DARK	P
8520 014100	14 STR PVC WHT/BLK	100	1.9	WHITE/BLACK	A
8520 0141000	14 STR PVC WHT/BLK	1000	17	WHITE/BLACK	A
8520 015100	14 STR PVC WHT/RED	100	1.9	WHITE/RED	A
8520 0151000	14 STR PVC WHT/RED	1000	17	WHITE/RED	A
8520 016100	14 STR PVC WHT/GRN	100	1.9	WHITE/GREEN	A

8520 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

8520 0161000	14 STR PVC WHT/GRN	1000	17	WHITE/GREEN	A
8520 0171000	14 STR PVC WHT/YEL	1000	17	WHITE/YELLOW	A
8520 018100	14 STR PVC WHT/BLU	100	1.9	WHITE/BLUE	A
8520 0181000	14 STR PVC WHT/BLU	1000	17	WHITE/BLUE	A
8520 019100	14 STR PVC WHT/BRN	100	1.9	WHITE/BROWN	A
8520 0201000	14 STR PVC WHT/ORG	1000	17	WHITE/ORANGE	A

A = STOCKED STRIPE COLORS.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 10-06-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.