

8529 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

  	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

Tinned copper, PVC insulation, medium wall. The extruded PVC insulation is flame and ozone resistant. Inert to most chemicals, oils, and solvents. Covers single cond., PVC insulated hook-up wire for internal wiring of electrical and electronic equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	20
Stranding	Solid
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.017 in.

OVERALL:

Overall Nominal Diameter	.066 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
Military Specification	MIL-W-76C
MIL Spec Rating	1000 V, 80°C

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8529 001100	20 SOL PVC BRN	100	0.5	BROWN	
8529 0011000	20 SOL PVC BRN	1000	6	BROWN	P

8529 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

8529 002100	20 SOL PVC RED	100	0.5	RED	
8529 0021000	20 SOL PVC RED	1000	6	RED	P
8529 003100	20 SOL PVC ORG	100	0.5	ORANGE	
8529 0031000	20 SOL PVC ORG	1000	6	ORANGE	P
8529 004100	20 SOL PVC YEL	100	0.5	YELLOW	
8529 0041000	20 SOL PVC YEL	1000	6	YELLOW	P
8529 005100	20 SOL PVC GRN	100	0.5	GREEN, DARK	
8529 0051000	20 SOL PVC GRN	1000	6	GREEN, DARK	P
8529 006100	20 SOL PVC LBLU	100	0.5	BLUE, LIGHT	
8529 007100	20 SOL PVC VIO	100	0.5	VIOLET	
8529 0071000	20 SOL PVC VIO	1000	6	VIOLET	P
8529 008100	20 SOL PVC GRY	100	0.5	GRAY	
8529 0081000	20 SOL PVC GRY	1000	6	GRAY	P
8529 009100	20 SOL PVC WHT	100	0.5	WHITE	
8529 0091000	20 SOL PVC WHT	1000	6	WHITE	P
8529 010100	20 SOL PVC BLK	100	0.5	BLACK	
8529 0101000	20 SOL PVC BLK	1000	6	BLACK	P
8529 0131000	20 SOL PVC DBLU	1000	6	BLUE, DARK	P

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 10-06-2005

8529 Hook-up/Lead - (Type MW) MIL-W-76C-PVC

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.