


8760 Multi-Conductor - Shielded Twisted Pair Cable



Description:

18 AWG stranded (16x30) tinned copper conductors, polyethylene insulation, twisted pair, overall Beldfoil® shield (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PE - Polyethylene	.019

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire	Conductor Material
20	7x28		TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.028

Overall Cabling

Overall Nominal Diameter: 0.222 in.

Pair

Pair Color Code Chart:

Number	Color
1	Black & Clear

Pair Lay Length & Direction:

Lay Length (in.)	Twists/ft. (twist/ft)
2.500	4.800

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +60°C
UL Temperature Rating:	60°C (UL AWM Style 2092)
Bulk Cable Weight:	26.600 lbs/1000 ft.
Max. Recommended Pulling Tension:	62 lbs.
Min. Bend Radius (Install)/Minor Axis:	2.250 in.

8760 Multi-Conductor - Shielded Twisted Pair Cable

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2092 (300 V 60°C)
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88760, 87760 or 82760

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
57

Nom. Inductance:

Inductance (µH/ft)
.18

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
29.8

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
44

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.5

Max. Operating Voltage - UL:

Voltage
300 V RMS (UL AWM Style 2092)

Max. Recommended Current:

Current
5.2 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8760 060U1000	1,000 FT	28.000 LB	CHROME		2 #18 LDPE SH PVC
8760 060U500	500 FT	14.500 LB	CHROME		2 #18 LDPE SH PVC
8760 0601000	1,000 FT	26.000 LB	CHROME		2 #18 LDPE SH PVC
8760 06010000	10,000 FT	280.000 LB	CHROME	C Y	2 #18 LDPE SH PVC

8760 Multi-Conductor - Shielded Twisted Pair Cable

8760 0602000	2,000 FT	56.000 LB	CHROME	C	2 #18 LDPE SH PVC
8760 060250	250 FT	7.250 LB	CHROME		2 #18 LDPE SH PVC
8760 060500	500 FT	14.500 LB	CHROME	C	2 #18 LDPE SH PVC
8760 0605000	5,000 FT	150.000 LB	CHROME	C	2 #18 LDPE SH PVC
8760 0609999	1,000 FT	26.000 LB	CHROME		2 #18 LDPE SH PVC

Notes:

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN.MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Line Level Analog Audio Cable

Single-Pair Cables



Belden analog audio cables are used for connecting line level audio equipment in either permanent or semi-permanent installations. They consist of one or two individually foil-shielded, twisted pairs. Once installed, they are not intended to be moved while in service. For cables that are in motion during use, refer to the Microphone and Musical Instrument Cable section in this catalog.

no. 8451 utilizes a paper tape separator to facilitate easy long length jacket stripping. Part no. 9451 comes with a bonded Beldfoil® shield so that the shield and jacket strip simultaneously. A special matte PVC jacket material is employed on part no. 1508A making it a highly flexible construction. Double pair cables are available in a round construction (part no. 8723) or in a ZIP cord style (part no. 1504A) for easy separation in two-channel or stereo hook-ups.

Belden's analog audio cable offering consists of a selection of designs to handle a variety of audio applications. Belden part

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

24 AWG Stranded (7x32) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire

Polypropylene Insulation • PVC Jacket (Available in Brown, Red, Green, Lt. Blue, Purple, Gray, White or Black)

300V RMS 60°C	1883A	NEC: CMR CEC: CMG FT4	1	Black, Red	U-1000 1000 [▲]	U-304.8 304.8	11.0 11.0	5.0 5.0	.008 .20	.020 .51	.123 3.12	31 102	58 190				
---------------	--------------	--------------------------------	---	---------------	-----------------------------	------------------	--------------	------------	-------------	-------------	--------------	-----------	-----------	--	--	--	--



▲1000 ft. put-up available in Gray only.

Jacket and shield are bonded so both can be removed with automatic stripping equipment.

For cross-connect use with 1408R (et al.) Snake Cables, see page 19.18.

Polyolefin Insulation • Black Matte PVC Jacket

High-Flex 300V RMS 60°C	1508A	NEC: CM CEC: CM	1	Black, Red	500 1000	152.4 304.8	6.5 11.0	2.9 5.0	.008 .20	.024 .61	.131 3.33	31 102	58 190				
----------------------------	--------------	--------------------------	---	---------------	-------------	----------------	-------------	------------	-------------	-------------	--------------	-----------	-----------	--	--	--	--



Jacket and shield are bonded so both can be removed with automatic stripping equipment.

For cross-connect use with 1408R (et al.) Snake Cables, see page 19.18.

24 AWG Stranded (7x32) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage)^{††} • 24 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	8641	NEC: CM CEC: CM	1	Black, Clear	100 U-500 500 U-1000 1000 2000	30.5 U-152.4 152.4 U-304.8 304.8 609.6	2.3 7.5 3.4 7.0 3.2 14.0 6.4 14.0 6.4 28.0	1.0 3.4 3.2 6.4 6.4 12.7	.016 .41	.025 .64	.168 4.27	22 72	42 138				
---	-------------	--------------------------	---	-----------------	---	---	---	---	-------------	-------------	--------------	----------	-----------	--	--	--	--



For Plenum versions of 8641, see 88641 or 82641.

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 200°C, Non-conduit	88641	NEC: CMP CEC: CMP FT6	1	Black, Red	100 500 [†] 1000 [†]	30.5 152.4 304.8	2.4 6.0 9.0	1.1 2.7 4.1	.006 .15	.014 .36	.106 2.69	31 102	59 194				
-----------------------------	--------------	--------------------------------	---	---------------	--	------------------------	-------------------	-------------------	-------------	-------------	--------------	-----------	-----------	--	--	--	--



Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 60°C, Non-conduit	82641	NEC: CMP CEC: CMP FT6	1	Black, Red	U-1000 ^{††} 1000 ^{††}	U-304.8 304.8	9.0 8.0	4.1 3.6	.006 .15	.014 .36	.106 2.69	31 102	59 194				
----------------------------	--------------	--------------------------------	---	---------------	--	------------------	------------	------------	-------------	-------------	--------------	-----------	-----------	--	--	--	--



FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

[†]Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.

^{††}Length may vary ±10% for UnReel.

Line Level Analog Audio Cable

Single-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

18 AWG Stranded (16x30) TC Conductors • Twisted Pair • Overall Beldfoil® Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire


Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	9460	NEC:	1	Black, Clear	U-500	U-152.4	18.5	8.4	.019	.48	.030	.76	.230	5.84	30	98	44	144			
		CM			U-1000	U-304.8	36.0	16.4													
		CEC:																			
		CM																			



The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of foil shield.

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	8760	NEC:	1	Black, Clear	250	76.2	6.8	3.1	.019	.48	.028	.71	.222	5.64	30	98	44	144			
		CM			U-500	U-152.4	13.5	6.1													
		CEC:			500	152.4	13.0	5.9													
		CM			U-1000	U-304.8	25.0	11.3													
					1000	304.8	26.0	11.8													
					2000	609.6	50.0	22.7													
					5000	1524.0	135.0	61.4													
	10000	3048.0	260.0	118.2																	



Shorting Fold

For Plenum versions of 8760, see 88760, 87760 or 82760.

18 AWG Stranded (19x30) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 200°C	88760	NEC:	1	Black, Red	100	30.5	3.7	1.7	.007	.18	.014	.36	.153	3.89	51	167	97	318	
		CMP			U-500†	U-152.4	12.5	5.7											
		CEC:			500†	152.4	11.0	5.0											
		CMP FT6			U-1000†	U-304.8	24.0	10.9											
		1000†	304.8	22.0	10.0														



Z-Fold®

Plenum • FEP Insulation • Red Fluorocopolymer Jacket

300V RMS 150°C	87760	NEC:	1	Black, Red	U-500†	U-152.4	12.5	5.7	.007	.18	.014	.36	.150	3.81	51	167	97	318
		CMP			500†	152.4	10.5	4.8										
		CEC:			1000†	304.8	21.0	9.5										
		CMP FT6																



Z-Fold®

Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 75°C	82760	NEC:	1	Black, Red	U-500†	U-152.4	12.0	5.5	.007	.18	.014	.36	.150	3.81	51	167	97	318
		CMP			U-1000††	U-304.8	22.0	10.0										
		CEC:			1000†	304.8	21.0	9.5										
		CMP FT6																



Z-Fold®

18 AWG Stranded (7x26) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (85% Coverage)

PVC Insulation • Chrome PVC Jacket

300V RMS 60°C	8790	NEC:	1	Red, White	U-500	U-152.4	17.5	7.9	.022	.56	.028	.71	.241	6.12	53	174	92	302
		CMG			500	152.4	17.0	7.7										
		CEC:			U-1000	U-304.8	33.0	15.0										
		CMG FT4			1000	304.8	35.0	15.9										



FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

*Capacitance between conductors.
 **Capacitance between one conductor and other conductors connected to shield.
 † Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.
 †† Spools and/or UnReel® cartons are one piece, but length may vary -0% to +10%.