

8917 Hook-up/Lead - UL AWM Style 1015

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	16
Stranding	26x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.030 in.

OVERALL:

Overall Nominal Diameter	.123 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	1015
UL Style	1230
UL Type	MTW
UL Rating	600 V, 105°C
CSA Type	AWM I A/B or TEW
CSA Rating	600 V, 105°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005

FLAME TEST:

UL Flame Test	VW-1
CSA Flame Test	FT1

PLENUM/NON-PLENUM:

8917 Hook-up/Lead - UL AWM Style 1015

Plenum (Y/N) N

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8917 001100	16 STR PVC BRN	100	2.1	BROWN	
8917 0011000	16 STR PVC BRN	1000	13	BROWN	P
8917 001500	16 STR PVC BRN	500	7.5	BROWN	
8917 001D1000	16 STR PVC BRN	D1000	13	BROWN	
8917 001D4000	16 STR PVC BRN	D4000	56	BROWN	
8917 001M1000	16 STR PVC BRN	M1000	15	BROWN	
8917 002100	16 STR PVC RED	100	2.1	RED	
8917 0021000	16 STR PVC RED	1000	13	RED	C P
8917 002500	16 STR PVC RED	500	7.5	RED	
8917 0025000	#16 STR PVC RED	5000	70	RED	C
8917 002D1000	16 STR PVC RED	D1000	13	RED	
8917 002D4000	16 STR PVC RED	D4000	56	RED	
8917 002M1000	16 STR PVC RED	M1000	15	RED	
8917 003100	16 STR PVC ORG	100	2.1	ORANGE	
8917 0031000	16 STR PVC ORG	1000	13	ORANGE	P
8917 003D1000	16 STR PVC ORG	D1000	0	ORANGE	
8917 003D4000	16 STR PVC ORG	D4000	56	ORANGE	
8917 004100	16 STR PVC YEL	100	2.1	YELLOW	
8917 0041000	16 STR PVC YEL	1000	13	YELLOW	C P
8917 004D1000	16 STR PVC YEL	D1000	0	YELLOW	
8917 004D4000	16 STR PVC YEL	D4000	56	YELLOW	
8917 005100	16 STR PVC DGRN	100	2.1	GREEN, DARK	
8917 0051000	16 STR PVC DGRN	1000	13	GREEN, DARK	P
8917 005500	16 STR PVC DGRN	500	7.5	GREEN, DARK	
8917 005D1000	16 STR PVC DGRN	D1000	13	GREEN, DARK	

8917 Hook-up/Lead - UL AWM Style 1015

8917 005D4000	16 STR PVC DGRN	D4000	56	GREEN, DARK	
8917 005M1000	16 STR PVC DGRN	M1000	15	GREEN, DARK	
8917 006D1000	16 STR PVC LBLU	D1000	13	BLUE, LIGHT	
8917 006D4000	16 STR PVC LBLU	D4000	56	BLUE, LIGHT	
8917 006M1000	16 STR PVC LBLU	M1000	15	BLUE, LIGHT	
8917 0071000	#16 STR PVC VIO	1000	13	VIOLET	P
8917 0081000	#16 STR PVC GRY	1000	13	GRAY	C P
8917 008D1000	16 STR PVC GRY	D1000	13	GRAY	
8917 008D4000	16 STR PVC GRY	D4000	56	GRAY	
8917 008M1000	16 STR PVC GRY	M1000	15	GRAY	
8917 009100	16 STR PVC WHT	100	2.1	WHITE	
8917 0091000	16 STR PVC WHT	1000	13	WHITE	P
8917 009500	16 STR PVC WHT	500	7.5	WHITE	
8917 0095000	#16 STR PVC WHT	5000	70	WHITE	C
8917 009D1000	16 STR PVC WHT	D1000	13	WHITE	
8917 009D4000	16 STR PVC WHT	D4000	56	WHITE	
8917 009M1000	16 STR PVC WHT	M1000	15	WHITE	
8917 010100	16 STR PVC BLK	100	2.1	BLACK	
8917 0101000	16 STR PVC BLK	1000	13	BLACK	P
8917 010500	16 STR PVC BLK	500	7.5	BLACK	
8917 0105000	#16 STR PVC BLK	5000	70	BLACK	C P
8917 010D1000	16 STR PVC BLK	D1000	13	BLACK	
8917 010D4000	16 STR PVC BLK	D4000	56	BLACK	
8917 010M1000	16 STR PVC BLK	M1000	15	BLACK	
8917 013100	16 STR PVC DBLU	100	2.1	BLUE, DARK	
8917 0131000	16 STR PVC DBLU	1000	15	BLUE, DARK	P
8917 013500	16 STR PVC DBLU	500	7.5	BLUE, DARK	
8917 0135000	#16 STR PVC DBLU	5000	70	BLUE, DARK	C

8917 Hook-up/Lead - UL AWM Style 1015

8917 189100	16 STR PVC GRN/YEL	100	2.1	GREEN/YELLOW	A
8917 1891000	16 STR PVC GRN/YEL	1000	13	GREEN/YELLOW	C A
8917 189D1000	16 STR PVC GRN/YEL	D1000	13	GREEN/YELLOW	
8917 189D4000	16 STR PVC GRN/YEL	D4000	56	GREEN/YELLOW	
8917 189M1000	16 STR PVC GRN/YEL	M1000	15	GREEN/YELLOW	

A = STOCKED STRIPE COLORS.

C = CRATE REEL PUT-UP.

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Revision Number: 1 Revision Date: 11-17-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.