



8917 Hook-up/Lead - UL Style 1015 CSA Type TEW

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

Tinned Copper, PVC insulated. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	16
Stranding	26x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.030 in.

OVERALL:

Overall Nominal Diameter	.123 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	1015
UL Rating	600 V, 105°C
CSA Type	TEW
CSA Rating	600 V, 105°C
Other Specification	JQA-F-

FLAME TEST:

UL Flame Test	VW-1
---------------	------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

PUT-UPS AND COLORS:

8917 Hook-up/Lead - UL Style 1015 CSA Type TEW

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8917 001100	16 STR PVC BRN	100	2.2	BROWN	
8917 0011000	16 STR PVC BRN	1000	15	BROWN	P
8917 001500	16 STR PVC BRN	500	7.5	BROWN	
8917 0015000	#16 STR PVC BRN	5000	70	BROWN	C
8917 002100	16 STR PVC RED	100	2.2	RED	
8917 0021000	16 STR PVC RED	1000	15	RED	C P
8917 002500	16 STR PVC RED	500	7.5	RED	
8917 0025000	#16 STR PVC RED	5000	70	RED	C
8917 003100	16 STR PVC ORG	100	2.2	ORANGE	
8917 0031000	16 STR PVC ORG	1000	15	ORANGE	P
8917 003500	16 STR PVC ORG	500	7.5	ORANGE	
8917 004100	16 STR PVC YEL	100	2.2	YELLOW	
8917 0041000	16 STR PVC YEL	1000	15	YELLOW	C P
8917 004500	16 STR PVC YEL	500	7.5	YELLOW	
8917 005100	16 STR PVC DGRN	100	2.2	GREEN, DARK	
8917 0051000	16 STR PVC DGRN	1000	15	GREEN, DARK	P
8917 005500	16 STR PVC DGRN	500	7.5	GREEN, DARK	
8917 0055000	#16 STR PVC DGRN	5000	70	GREEN, DARK	P
8917 0071000	#16 STR PVC VIO	1000	15	VIOLET	P
8917 0081000	#16 STR PVC GRY	1000	15	GRAY	C P
8917 009100	16 STR PVC WHT	100	2.2	WHITE	
8917 0091000	16 STR PVC WHT	1000	15	WHITE	P
8917 009500	16 STR PVC WHT	500	7.5	WHITE	
8917 0095000	#16 STR PVC WHT	5000	70	WHITE	C
8917 010100	16 STR PVC BLK	100	2.2	BLACK	
8917 0101000	16 STR PVC BLK	1000	15	BLACK	P



8917 Hook-up/Lead - UL Style 1015 CSA Type TEW

8917 010500	16 STR PVC BLK	500	7.5	BLACK	
8917 0105000	#16 STR PVC BLK	5000	70	BLACK	C P
8917 013100	16 STR PVC DBLU	100	2.2	BLUE, DARK	
8917 0131000	16 STR PVC DBLU	1000	15	BLUE, DARK	P
8917 013500	16 STR PVC DBLU	500	7.5	BLUE, DARK	
8917 0135000	#16 STR PVC DBLU	5000	70	BLUE, DARK	C
8917 189100	16 STR PVC GRN/YEL	100	2.2	GREEN/YELLOW	A
8917 1891000	16 STR PVC GRN/YEL	1000	15	GREEN/YELLOW	C A
8917 1894000	16 STR PVC GRN/YEL	4000	60	GREEN/YELLOW	A K Z

A = STOCKED STRIPE COLORS.

C = CRATE REEL PUT-UP.

K = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 500'

P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR 1 OR 2 STRIPES. 10 000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL WITH A MINIMUM LENGTH OF 100'.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 09-05-2002

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.